

CMB-170

Barebone system support Intel® Atom Dual Core processor



Features

dh

Form Factor	Bare-bone system for Pico-ITX motherboard
Construction	Heavy-Duty steel
Mini-ITX Board / CPU	Inside Motherboard : LP-170C Onboard CPU : Intel® Atom™ D525 dual-core processor
Drive Bay	Internal : 1 x 2.5" HDD Space , 1 x CF card socket
Extensive slot	1 x Mini-PCle socket for wifi card
Thermal Control	One 5 cm system cooling Fan
Front Panel	Power on switch LED indicator for Power and HDD activity Mic-in / Ear phone , 2 x USB
Rear Side I/O	2 x COM , 2 x USB , 1 x LAN , 1 x VGA , 1 x PS/2 Key/Mouse 1 x DC input , 1 x antenna , 1 x DVI (Optional)
Environment	Operating Temperature: 0 ~ 50°C
Power supply	12V/ 80W adapter
Dimension	125 x 90 x 80 mm

Ordering Guide

CMB-170C	Barebone with LP-170C motherboard , 12V/80W adapter
ADP-L2DXT	LVDS to DVI convert module
Memory	DDR2 667 MHz SO-DIMM for 1.0GB / 2.0 GB / 4.0 GB
Storage device	2.5" SATA HDD or CompactFlash card