

BROOKFIELD PROCESS VISCOMETERS/RHEOMETERS

BF35 Viscometer™

measures viscosity of oil drilling and fracturing fluids at atmospheric pressure in both field and laboratory settings

Easy speed changes with convenient control knob

Shear Stress Values Displayed on easy-to-read lighted magnified dial

Maintains a constant shear rate under varying input power and drilling fluid conditions. Provides drilling fluid engineers with an accurate and versatile tool.

Conventional oilfield rotor, bob and torsion spring maintain rheology history and reproducibility between instruments and laboratories

Sample Cup

Adjustable table height to accommodate a variety of beaker/containment sizes

Specifications/Features

Motor Speeds:	8 fixed (3, 6, 30, 60, 100, 200, 300, 600)
Speed Accuracy:	0.001 (rpm)
Readout:	Direct dial with light
Heat Cup:	Stainless steel, 150 Watt, 190°F (88°C) maximum recommended temperature
Geometry:	True Couette Coaxial Cylinder
Power:	97-250 VAC, 50/60 Hz (12 volt operation requires special cable)
Carrying Case	Included

BROOKFIELD
ISO 9001 CERTIFIED
BROOKFIELD ENGINEERING LABS., INC.

(ES) Equipements Scientifiques SA - Département Bio-tests & Industries - 127 rue de Buzenval BP 26 - 92380 Garches
Tél. 01 47 95 99 90 - Fax. 01 47 01 16 22 - e-mail: bio@es-france.com - Site Web: www.es-france.com