

# 3M™ Multi-Touch Display C4667PW

## Interactive Digital Signage with Truly Uncompromised Touch

The interactive 46-inch **3M™ Multi-Touch Display C4667PW** features 3M's high-performance projected capacitive (3M PCT) multi-touch technology and sophisticated bezel-free display design to offer users a truly uncompromised touch experience. The C4667PW chassis display delivers 60 simultaneous touches over 1,000 square inches of interactive surface area, at an ultra-fast 12 ms response time, to enable designers to create multi-user experiences that are more natural, intuitive and responsive when compared to infrared- and optical-based systems. Versatile enough for interactive digital signage, interactive tables and kiosk solutions, the C4667PW provides system architects with a high-performance, easy-to-integrate commercial display for innovative multi-touch solutions.



### Precision Large-format Multi-Touch

In addition to delivering 60 simultaneous touches at a 12ms response time, the 3M touch electronics have an advanced built-in palm rejection algorithm to ensure that unintended contact with the screen is ignored and does not interfere with the user's intended action. The design of the projected capacitive sensor has more than 10,000 touch sensing points in close proximity, making it precise and extremely accurate across the entire touchscreen. 3M PCT's durable glass surface has unique anti-stiction properties that greatly reduces surface friction and allows users fingers to effortlessly glide across the display for easy gesture functions. This fast, accurate, and easy to use multi-touch screen enables customers to create, deliver and experience innovative and engaging multi-user applications.

### Industrial Grade Designed for Multi-Touch Interaction

The C4667PW display has been designed from the ground up to meet the unique requirements of a large format multi-touch display. Unlike televisions or digital signs, an interactive multi-touch display draws users in close proximity to the LCD. To maintain sharp image quality at close distances the C4667PW display features a full 1080p HD LCD, wide viewing angles, and a fine pixel pitch of 0.177mm x 0.530mm. An advanced thermal management system ensures the touch surface is at a comfortable temperature for the user, even in a horizontal table implementation, and promotes "always on" performance of critical electronic components. To ensure the image

### Recommended Multi-Touch Applications

- Interactive Digital Signage
- Transportation
- Wayfinding
- Security Monitoring Systems
- Training and Simulation
- Tele-presence
- Retail Product Selectors
- Ticketing/Vending
- Point of Information
- Pro Audio/Visual
- Geospatial
- Broadcast

quality is not compromised in strong ambient lighting environments, this display features an anti-glare coating.

Every element of the C4667PW is designed to enable integrators to configure the display in any orientation while meeting the demanding needs of public environments. The LED backlight system allows integrators to implement in landscape, portrait or horizontal orientations without concern of non-uniformity that CCFL systems can exhibit. At just 2.7" deep the C4667PW can be a sleek wall mounted interactive digital sign or a slim interactive table or kiosk. The all glass bezel free industrial design, inspired by modern consumer devices, makes it an elegant addition for any commercial or professional environment.

Feature	Benefit
3M PCT Multi-Touch Technology	<ul style="list-style-type: none"><li>• 60 finger multi-touch input enables intuitive on-screen collaboration</li><li>• Fast &lt;12 millisecond touch response creates a natural, intuitive and responsive interface</li><li>• Advanced palm rejection algorithms prevent unintended touches that commonly occur in table applications</li><li>• Anti-stiction surface enhances the user experience for simple and advanced gestures</li></ul>
Sophisticated and Durable Design	<ul style="list-style-type: none"><li>• Flat front surface design built in for elegant modern aesthetics</li><li>• Slim 2.7" thickness provides sleek low profile appearance while enabling easy integration on wall, table or enclosure</li><li>• All metal construction provides rugged frame for public use environments</li><li>• Advanced thermal management system designed to keep display cool to the touch in tabletop and enclosure installations</li><li>• Anti-Glare Coating to maintain image quality under harsh ambient lighting</li></ul>
Premium Display for Multi-Touch Applications	<ul style="list-style-type: none"><li>• Full HD resolution (1920x1080) with a fine pixel pitch to maintain sharp image quality while performing up-close interactions</li><li>• Ultra-Wide viewing angle presents a brilliant image at any angle</li><li>• LED Backlights present a long lasting, bright, uniform image regardless of integrated orientation</li></ul>



# 3M™ Multi-Touch Display C4667PW Specifications

## Functional Specifications

### Display Details

LCD Technology	SPVA (super pattern vertical align)
Display Colors	1.07 billion
Pixel Pitch	.177 x .530mm
Brightness	700 cd/m2 (nit) typical
with touch sensor (max.)(1)	610 cd/m2 (nit) typical
Contrast Ratio (2)	4000:1 typical
Viewing Angle	Horizontal/Vertical: 178 degrees typical
Video Response Time (3)	13 ms typical
Refresh Rate	60Hz
Control Type	OSD
Native Resolution	1920 x 1080

(1) Brightness measured on a display with 3M™ Projected Capacitive sensor.

(2) Measured at a contrast ratio of 10.

(3) Gray to Gray

### Touch Details

Number of Touch Points	60 points with palm rejection
Touch Point Speed (4)	<12 milliseconds
Input Type	Finger, thin glove
Touch Communication	USB
Operating System Support	Windows 8 / 7 / Vista / XP, Linux, Mac

(4) up to 20 touches

## Physical Specifications

### Product Details

Operating Environment	0 to +40 degrees C, relative humidity, non-condensing 90%
Storage Environment	-10 to +60 degrees C
Video Input	DVI, VGA, HDMI, DP (HDCP)
Audio	Speaker: 5W + 5W @ 8Ω Headphone: 20mW + 20mW @ 32Ω
Cover Glass	Chemically-strengthened
VESA Pattern	400mm x 400mm
Power Supply	Internal 110/220 VAC Power Supply
Power Consumption	165 watt (maximum)
RoHS Compliant	Yes
Agency Approvals	FCC-B, CE, TUV (IEC 60950), C-TICK
Warranty	2 years

### Dimensions and Weight

Display Area (WxH) (viewing area)	1018.08 x 572.67mm 40.08 x 22.55 inches
Display Dimensions (outer)	1086.7 x 638.3 x 68.6 mm 42.8 x 25.1 x 2.7 inches
Packaging (WxHxD)	1240 x 880 x 250 mm 48.8 x 34.6 x 9.8 inches
Display weight	26 kg / 57 lbs
Packaging/Display weight	31.6 kg / 70 lbs

### Ordering Information

Part Number	98-0003-4107-7
-------------	----------------

## Connections



### 3M Touch Systems

Subsidiary of 3M Company  
501 Griffin Brook Park Drive  
Methuen, MA 01844 U.S.A.

1-888-659-1080

[www.3m.com/touch](http://www.3m.com/touch)

**RoHS Directive compliant:** RoHS 2011/65/EU means that the product or part does not contain any of the substances in excess of the maximum concentration values ("MCVs") in EU RoHS Directive 2011/65/EU, unless the substance is in an application that is exempt under EU RoHS. The MCVs are by weight in homogeneous materials. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M. (3/13)

**IMPORTANT NOTICE TO PURCHASER:** Specifications are subject to change without notice. These 3M Touch Systems' Products and software are warranted to meet their published specifications from the date of shipment and for the period stated in the specification. 3M Touch Systems makes no additional warranties, express or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose. User is responsible for determining whether the 3M Touch Systems Products and software are fit for User's particular purpose and suitable for its method of production, including intellectual property liability for User's application. If the Product, software or software media is proven not to have met 3M Touch Systems' warranty, then 3M Touch Systems' sole obligation and User's and Purchaser's exclusive remedy, will be, at 3M Touch Systems' option, to repair or replace that Product quantity or software mediator to refund its purchase price. 3M Touch Systems has no obligation under 3M Touch Systems' warranty for any Product, software or software media that has been modified or damaged through misuse, accident, neglect, or subsequent manufacturing operations or assemblies by anyone other than 3M Touch Systems. 3M Touch Systems shall not be liable in any action against it in any way related to the Products or software for any loss or damages, whether non-specified direct, indirect, special, incidental or consequential (including downtime, loss of profits or goodwill) regardless of the legal theory asserted. (7/02)



© 3M 2014 All Rights Reserved. 3M is a trademark of 3M Company.

C4267PW-0114

(ES) Equipements Scientifiques SA - Département Informatique & Vidéo - 127 rue de Buzenval BP 26 - 92380 Garches  
Tél. 01 47 95 99 71 - Fax. 01 47 01 16 22 - e-mail: [inf@es-france.com](mailto:inf@es-france.com) - Site Web: [www.es-france.com](http://www.es-france.com)