

## Coaxial Panel Connector 23\_C-50-0-2/133\_N

### Description

Straight panel receptacle jack, flange mount

Interface standards

IEC 60169-7\_MIL-STD-348A/302



### Technical Data

#### Electrical Data

|                          |             |
|--------------------------|-------------|
| Impedance                | 50 $\Omega$ |
| Interface frequency max. | 11 GHz      |

#### Mechanical Data

|                   |           |
|-------------------|-----------|
| Number of matings | 500       |
| Weight            | 0.0227 kg |

#### Environmental Data

|  |                               |
|--|-------------------------------|
| Operating temperature<br>2011/65/EU (RoHS - including<br>2015/863 and 2017/2102) | -65 °C to 165 °C<br>compliant |
|--|-------------------------------|

#### Material Data

| Piece Parts    | Material               | Surface Plating        |
|----------------|------------------------|------------------------|
| Centre contact | Copper Beryllium Alloy | SUCOPRO / Gold Plating |
| Outer contact  | Brass                  | SUCOPLATE (R) Plating  |
| Body           | Brass                  | SUCOPLATE (R) Plating  |
| Insulator      | PFA / PTFE             |                        |

### Related Documents

|                   |              |
|-------------------|--------------|
| Outline drawing   | DOU-00010619 |
| Catalogue drawing | DCA-00198764 |

### Ordering Information

|                |                    |
|----------------|--------------------|
| Single package | 23_C-50-0-2/133_NE |
|----------------|--------------------|

