

## Coaxial Cable Connector 24\_MCX-50-1-3/111\_N

### Description

Straight bulkhead cable feed through

Interface standards  
IEC 60169-36\_CECC 22220



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 6 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact soldered  
Weight 0.0017 kg

#### Environmental Data

Operating temperature -55 °C to 155 °C  
2011/65/EU (RoHS - including  
2015/863 and 2017/2102) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Fastening nut	Brass	Gold Plating (Nickel underplated)
Washer	Bronze	Gold Plating (Nickel underplated)

### Related Documents

Catalogue drawing DCA-00009973  
Assembly instruction DOC-0000389859  
Mounting hole DOU-00008855

### Ordering Information

Single package 24\_MCX-50-1-3/111\_NE

### Additional Information

Suitable cables EZ\_47\_TP\_M17, SUCOFORM\_47\_CU

