

Coaxial Cable Connector 21_4310-50-12-60/033_-

Description

Straight cable jack

Interface standards

IEC 61169-54



Technical Data

Electrical Data

Impedance	50 Ω	
Interface frequency max.	12 GHz	
Frequency range	DC to 2.7 GHz	2.7 to 3.7 GHz
Return loss	32 dB	30 dB

Mechanical Data

Centre contact	plugged
Outer contact	clamped
Weight	0.1212 kg

Environmental Data

Operating temperature	-55 °C to 85 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Silver Plating
Outer contact	Bronze	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Other body part	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing	DOU-00305322
Catalogue drawing	DCA-00305326
Assembly instruction	DOC-0000799919

Ordering Information

Single package	21_4310-50-12-60/033_-E
----------------	-------------------------

Additional Information

Suitable cables	SUCOFEED_1/2_PW, SUCOFEED_1/2, SUCOFEED_1/2_FR, SUCOFEED_1/2_LW
-----------------	---

Remarks

Other suitable cables: RFS CELLFLEX LCF12-50J, LCF12-50JFN, ICA12-50JPLW, ICA12-50JPLLW, ICA12-50JPL / ANDREW/ COMMSCOPE LDF4-50A / Assembly instructions: Foam-DOC-0000799919, Plenum-DOC-0000736630 / Note: Use blade unit 74_Z-0-12-21, 85068959 (colour green)



Data Sheet

HUBER+SUHNER

Coaxial Cable Connector

21_4310-50-12-60/033_-

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, AS/EN9100, ISO/TS 16949 and IRIS.

www.hubersuhner.com

Wichtig: Es sind keine technischen Zeichnungen oder Dokumente zum Download freigegeben!



ES France - Département RF & Hyperfréquences
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 60
Fax. 01 47 01 16 22



e-mail : hyper@es-france.com
Site Web : www.es-france.com