# **Data Sheet**

# HUBER+SUHNER

# Coaxial PCB Connector 85\_BNC-75-0-1/133\_N

## Description

Right angle PCB jack

Interface Standards Interface compatible with IEC 61169-8



### **Technical Data**

Electrical Data Impedance Interface frequency max.	75 Ω 1 GHz
Mechanical Data Board mounting type Weight	through holes 0.0152 kg
Environmental Data Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)	-65 °C to 165 °C compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

#### **Related Documents**

Outline drawing	DOU-00012866
Catalogue drawing	DCA-00012868
Mounting hole	DOU-00012084

#### **Ordering Information**


Single package

85\_BNC-75-0-1/133\_NE

#### Remarks

PCB connector with stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS





Tél. 01 47 95 99 60 Fax. 01 47 01 16 22

Ċ

