Data Sheet



Coaxial Cable Connector 16_BNC-75-4-2/133_N

Description

Right angle cable plug

Interface standards
Interface compatible with IEC 61169-8



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 75\,\Omega \\ \text{Interface frequency max.} & 1\,\text{GHz} \end{array}$

Mechanical Data

Centre contact soldered
Outer contact clamped
Weight 0.0232 kg

Environmental Data

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Catalogue drawing DOU-00006458
Assembly instruction DOC-0000179477

Ordering Information

Single package 16_BNC-75-4-2/133_NE

Additional Information

Suitable cables RG_59_B/U, GX_04273

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.