

# ISCH0706-WVA0LO

## Specification

IP65 front Stainless Chassis, 7" LCD monitor, 800 x 480, LED 1000 nits, VGA input



### Features

- IP65 front side sealed for water-dust proof
- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers

|                     |                                                                                          |                                                             |                                                         |  |
|---------------------|------------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------|--|
| Panel               | Cell Type / Glass Surface                                                                |                                                             | TFT LCD / Black Anti-Glare, low reflection coating      |  |
|                     | Aspect Ratio / Size                                                                      |                                                             | Wide / 7" viewable diagonal area                        |  |
|                     | Active Area / Pixel Pitch                                                                |                                                             | 152.40(H) x 91.44(V) mm / 0.1905(H) x 0.1905(V) mm      |  |
|                     | Native Resolution / Colors                                                               |                                                             | 800(H) x 480(V) / 262 K                                 |  |
|                     | Brightness / Contrast                                                                    |                                                             | 1000 cd/m <sup>2</sup> (typ) / 500 : 1                  |  |
|                     | Response Time                                                                            |                                                             | ≤ 30 ms                                                 |  |
|                     | Viewing Angle (typical)                                                                  |                                                             | H. 130° (- 65° ~ + 65°) , V. 110°(- 60° ~ + 50°)        |  |
|                     | Light Source                                                                             |                                                             | LED backlight, Long life, 35,000 hrs (typ)              |  |
| Input Sources       | PC System                                                                                | Signal                                                      | Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)         |  |
|                     |                                                                                          | Sync                                                        | Separate Sync, Composite Sync, Sync On Green            |  |
|                     |                                                                                          | Frequency                                                   | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz |  |
|                     | Audio System                                                                             |                                                             | 2W speaker x 2                                          |  |
| Input Terminals     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug |                                                             |                                                         |  |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)               |                                                             |                                                         |  |
|                     | OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)        |                                                             |                                                         |  |
| Power               | 12V DC in                                                                                |                                                             |                                                         |  |
| Power Consumption   | Operation / Power Saving                                                                 | 10 watt , < 2 watt (Support DPMS)                           |                                                         |  |
| Operating Condition | Temperature / Humidity                                                                   | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)     |                                                         |  |
| Storage Condition   | Temperature / Humidity                                                                   | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) |                                                         |  |
| Certification       |                                                                                          | FCC , CE                                                    |                                                         |  |
| Dimensions          | Physical                                                                                 | Please refer to Drawing                                     |                                                         |  |
|                     | Carton                                                                                   | W x H x D = TBD                                             |                                                         |  |
| Weight              | N.W. / G.W.                                                                              | 3 Kgs / 4 Kgs                                               |                                                         |  |
| Container Loaded    | 20ft / 40ft / 40ft HQ                                                                    | TBD (Sets , By pallet)                                      |                                                         |  |

|         |                  |                      |                          |                              |
|---------|------------------|----------------------|--------------------------|------------------------------|
| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | Infrared touch   | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Protected glass  |                      | Sunlight Readable        | Light Sensor                 |
|         |                  |                      |                          | Auto-Dimming                 |