

ISCH0706-WS35L1

Specification

IP65 front Stainless Chassis, 7" LCD monitor, 1024 x 600, LED 350 nits, VGA input, wide temperature



Features

- IP65 front side sealed for water-dust proof
- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers

Panel	Cell Type / Glass Surface		TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size		Wide / 7" viewable diagonal area	
	Active Area / Pixel Pitch		153.60(H) x 90(V) mm / 0.150(H) x 0.150(V) mm	
	Native Resolution / Colors		1024(H) x 600(V) / 262 K	
	Brightness / Contrast		350 cd/m ² (typ) / 700 : 1	
	Response Time		≤ 16 ms	
	Viewing Angle (typical)		H. 150° (- 75° ~ + 75°) , V. 140°(- 75° ~ + 65°)	
	Light Source		LED backlight, Long life, 35,000 hrs (typ)	
Input Sources	PC System		Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)
			Sync	Separate Sync, Composite Sync, Sync On Green
			Frequency	F _h : 30 - 82Khz , F _v : 50 -75Hz
	Audio System		2W speaker x 2	
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug			
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)			
	OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)			
Power	12V DC in			
Power Consumption	Operation / Power Saving	9.625 watt , < 2 watt (Support DPMS)		
Operating Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)		
Storage Condition	Temperature / Humidity	- 30°C ~ 80°C (- 22°F ~ 176°F) , 10% ~ 90% (no condensation)		
Certification			FCC , CE	
Dimensions	Physical		Please refer to Drawing	
	Carton		W x H x D = TBD	
Weight	N.W. / G.W.		3 Kgs / 4 Kgs	
Container Loaded	20ft / 40ft / 40ft HQ		TBD (Sets , By pallet)	

Options	Touch	Video / TV	Enhanced Panel	Others
	Resistive touch	SV + AV	Panel with LED backlight	Digital Signage(Stand alone)
	Capacitive touch	SV + AV + AV_Looping	High brightness panel	Networking Digital Signage
	Infrared touch	SV + AV + TV	Wide Temperature	Motion Sensor
	Protected glass		Sunlight Readable	Light Sensor
				Auto-Dimming