

LUX SENSOR



- ① measures light in a building environment
- ② IP68 casing
- ③ up to 7 years of battery life
- ④ data transmission every 1, 2, 5, 10 minutes



ambient light detection in all kind of building environment – offices, retail spaces, conference rooms and other places that require coordinated lighting solutions.

Aranet LUX Sensor	
Measurements	Illuminance
Line of Sight Range	3km / 1.9mi
Operating environment	Indoor and Outdoor use
Transmitter power	14 dBm
Frequency	Depends on base station instructions
Measurement range	0 - 200 000 lux
Measurement resolution	1 lux
Measurement accuracy	+/- 10%
Data Transmission	1, 2, 5, 10 minutes
Data Protection	Data encryption
Power options	1 AA Alkaline batteries (Zn/MnO ₂) 1 AA Lithium batteries (Li/FeS ₂)
Battery life @20°C / 68°F	Up to 5 years with Alkaline batteries Up to 7 years with Lithium batteries
Operating temperature	-20°C to 55°C / -4°F to 131°F with Alkaline batteries -40°C to 60°C / -40°F to 140°F with Lithium batteries
Operating humidity	0% to 100%
Dimensions	Sensor body - 35mmØ x 117mm
Weight	80g w Alkaline battery 72g w Lithium battery
Construction	ASA Plastic + Aluminium
Protection class	IP68
Marking	CE
Compatible base stations	Aranet PRO
Included	1 AA Alkaline battery

For more detailed information about Aranet products, please visit www.aranet.com, contact us info@aranet.com or your Aranet representative.

(ES) Equipements Scientifiques SA - Département Bio-tests & Industries - 127 rue de Buzenval BP 26 - 92380 Garches
Tél. 01 47 95 99 90 - Fax. 01 47 01 16 22 - e-mail: bio@es-france.com - Site Web: www.es-france.com