

FTB-4 Pro Platform

VERSATILE MULTITECHNOLOGY PORTABLE TEST PLATFORM



PART OF THE
EXFO | FTB Ecosystem



Feature(s) of this product is/are protected by one or more of: US design patents D739,277; D763,713; and D798,171 and equivalent(s) in other countries.

The most flexible solution to test multiple technologies and high speed networks.

SPEC SHEET

KEY FEATURES

Connects anywhere: USB, WiFi, Bluetooth, mobile and virtual private network (VPN)

Loaded with utilities: equipped with all the tools required to maximize field testing

Like a PC: quad-core processor with Windows 10 operating system

EXFO Connect-compatible: automated asset management; data goes through the cloud and into a dynamic database

RELATED PRODUCTS



Fiber Inspector Probe
FIP-400B (WiFi or USB)



THE POWER AND FLEXIBILITY YOU NEED FOR ADVANCED APPLICATIONS

The FTB-4 Pro delivers all the power of a high-end platform in a go-where-you-need field-testing tool.

APPLICATIONS

ROADM and PTN turn-up testing

Combines SONET/SDH, OTN, Ethernet and Fibre Channel analysis, as well as an optical spectrum analyzer (OSA) with built-in polarization controller.

Gigabit/10 Gigabit Ethernet configurations

Gigabit Ethernet analyzer, OTDR and optical spectrum analyzer with polarization controller.

Fibre Channel

Fibre Channel is the protocol for the communication structure dedicated to carrying different types of traffic for applications that require first-rate capabilities of storage and technologies.

ROADM commissioning

Insert an OSA within this compact, portable solution for fast and accurate DWDM commissioning and turn up of high-speed networks up to 100/200/400 Gbit/s.

Multiservice testing

Easily turn up, validate and troubleshoot DS_n/PDH, SONET/SDH and Ethernet services up to 10 Gbit/s in converged optical networks. Delivering IPTV test capabilities and transmission control protocol (TCP) throughput assessment.

Fiber characterization and troubleshooting

OTDR/iOLM testing combined with fiber endface inspection and optical power measurement for fiber characterization and troubleshooting of any network, including access, LAN/WAN, data center, FTTx, metro, long-haul and ultra-long-haul.

FTTH testing

With a dynamic range of up to 42 dB and enabling power meter and visual fault locator functionalities, the PON FTTx/MDU OTDR module allows fiber installers to seamlessly characterize splitters in PON FTTx and multiple dwelling unit (MDU) applications.

Ethernet testing from 10 Mbit/s to 100 Gbit/s

100% line-rate testing of IP traffic at up to 100G; RFC 2544 and ITU-T Y.1564 Ethernet service activation with full statistics, and packet capture, traffic filtering, ping and traceroute with clear pass/fail verdicts.

CWDM turn-up testing

Integrate CWDM OTDR to test through CWDM-based mux/demux at ITU-recommended wavelengths.

DWDM testing

Highly accurate and reliable DWDM network commissioning, troubleshooting and channel analysis.

100+ Gbit/s testing applications

Advanced future-proof hardware, ready for today's and tomorrow's 100+ Gbit/s applications.

Distributed PMD analysis

Single-ended, span-by-span measurement of PMD, enabling targeted fiber upgrades and cost-effective deployment of transmission speeds at 10, 40 and 100 Gbit/s.

OPTICAL TEST MODULES

Optical channel analyzer	FTB-5230S-OCA
Optical spectrum analyzer	FTB-5230S FTB-5240S FTBx-5245 FTB-5240BP
OTDR	FTB-7200D FTB-7300E FTB-7400E FTB-7500E FTB-7600E FTBx-720C FTBx-730C FTBx-735C FTBx-750C
OTDR CWDM/DWDM	FTB-7400E FTBx-740C
OLTS	FTB-3930 FTBx-940 FTBx-945
Single-ended dispersion analyzer (CD/PMD)	FTB-5700
Chromatic dispersion (CD)	FTB-5800
Polarization mode dispersion (PMD)	FTB-5500B
Distributed PMD analyzer	FTB-5600

TRANSPORT AND DATACOM TEST MODULES

Multiservice	FTB-8830NGE
10M-to-100G high-speed multiservice	FTB-88100NGE
40G/100G high-speed multiservice	FTB-88100G
DS_n/PDH and SONET/SDH electrical	FTB-8805
Advanced 100G multiservice	FTBx-88200NGE
Versatile 10G multiservice	FTBx-8870 FTBx-8880



OPTICAL PLUG-AND-PLAY OPTIONS

The platform can host optical plug-and-play options that can be purchased whenever you need them, at the time of your order or later on. In either case, installation is a snap. You can do it by yourself. No software update required.

Optical Power Meter

A high-level power meter (GeX) that can measure up to 27 dBm, the highest in the industry. This is essential for HFC networks or high-power signals. If used with an auto-lambda/auto-switching compatible light source, the power meter automatically syncs on the same wavelength, avoiding any risk of mismatched measurement.

- › Extensive range of connectors
- › Auto-lambda and Auto-switching
- › Offers measurement storage and reporting
- › Choice of seven standard or CWDM calibrated wavelengths

Visual Fault Locator (VFL)

The plug-and-play VFL easily identifies breaks, bends, faulty connectors and splices, in addition to other causes of signal loss. Basic yet essential, this troubleshooting device should be part of every field technician's toolbox. Visually locating faults by creating a bright-red glow at the exact location of the fault on singlemode or multimode fibers, the VFL detects faults over distances of up to 5 km. (Available with the optical power meter only)



DO MORE!

The Windows 10 operating system allows for a wide choice of third-party applications and supports an extensive range of USB devices.

- › Start faster and multitask
- › Use the Office suite
- › Connect to printers, cameras, keyboards, mice, and more

Bring Your Own Apps



Share your desktop
(e.g., using
TeamViewer)



Antivirus
software



Communicate via
e-mail services
and over-the-top
(OTT) apps



Record and
automate
actions



Share files via
cloud-based
storage

EXFO

FIBER CONNECTOR INSPECTION AND CERTIFICATION— THE ESSENTIAL FIRST STEP BEFORE ANY OTDR TESTING

Taking the time to properly inspect a fiber-optic connector using an EXFO fiber inspection probe can prevent a host of issues from arising further down the line, thus saving you time, money and trouble.

The First Fully Automated Fiber Inspection Probe for the Field

Housing a unique automatic focus adjustment system, the FIP-430B USB and FIP-435B WiFi Probes automate each operation in the connector endface inspection sequence, transforming this critical process into one quick and easy step, which can be performed by technicians of all skill levels.

100%
Automated^a

1-step
process^a

57%
shorter test time^b



FIVE MODELS TO FIT YOUR BUDGET

FEATURES	USB WIRED			WIRELESS	
	Basic FIP-410B	Semi-Automated FIP-420B	Fully Automated FIP-430B	Semi-Automated FIP-425B	Fully Automated FIP-435B
Three magnification levels	✓	✓	✓	✓	✓
Image capture	✓	✓	✓	✓	✓
Five-megapixel CMOS capturing device	✓	✓	✓	✓	✓
Automatic fiber image-centering function	X	✓	✓	✓	✓
Automatic focus adjustment	X	X	✓	X	✓
Onboard pass/fail analysis	X	✓	✓	✓	✓
Pass/fail LED indicator	X	✓	✓	✓	✓
WiFi connectivity	X	X	X	✓	✓

For more information, visit www.EXFO.com/fiberinspection.

Notes

a. FIP-430B and FIP-435B models.

b. Data sourced from EXFO's case study, with calculation based on typical analysis time.



SOFTWARE TEST TOOLS

This series of platform-based software testing tools enhances the value of the FTB-4 Pro Platform, providing additional testing capabilities without the need for additional modules or units.

EXpert TEST TOOLS

EXpert VoIP TEST TOOLS

EXpert VoIP generates a voice-over-IP call directly from the test platform to validate performance during service turn-up and troubleshooting.

- › Supports a wide range of signaling protocols, including SIP, SCCP, H.248/Megaco and H.323
- › Supports mean-opinion-score (MOS) and R-factor quality metrics
- › Simplifies testing with configurable pass/fail thresholds and RTP metrics

EXpert IP TEST TOOLS

EXpert IP integrates six commonly used datacom test tools into one platform-based application to ensure that field technicians are prepared for a wide range of testing needs.

- › Rapidly performs debugging sequences with VLAN scan and LAN discovery
- › Validates end-to-end ping and traceroute
- › Verifies file transfer protocol (FTP) performance and hypertext-transfer-protocol (HTTP) availability

EXpert IPTV TEST TOOLS

This powerful Internet-protocol-television (IPTV) quality assessment solution enables set-top box emulation and passive monitoring of IPTV streams, allowing for quick and easy pass/fail verification of IPTV installations.

- › Real-time video preview
- › Analyzes up to 10 video streams
- › Comprehensive quality-of-service (QoS) and quality-of-experience (QoE) metrics, including the MOS score

THIRD-PARTY TEST TOOLS

Wireshark

This live-network packet-capture utility makes it possible to look *inside* the packets and obtain data, including transmission time, source, destination and protocol type. Users can then diagnose a problem or root out suspicious behavior.

SOFTWARE APPLICATIONS

ConnectorMax

Providing lightning-fast results in the first step of fiber-link testing, ConnectorMax2 is a powerful, platform-based, automated inspection application that delivers quick pass/fail assessment of connector endfaces, and which is specifically designed to save both time and money in the field.


FastReporter

Consolidated data management and post-processing tool designed to increase reporting productivity for connector endface inspection and all types of optical-layer testing: optical link mapper (iOLM), OTDR, ORL, loss, PMD and chromatic dispersion (CD).



CONNECTED ANYWHERE, ANYTIME

The value of connectivity resides in the ability to connect your platform anywhere, at any time. This is why we've equipped our platforms with technology offering unprecedented flexibility. Whether you need to transfer data to the cloud or interface with a smart device, you'll have the capability needed.



Bluetooth® WiFi 3G GPS



Secure VPN communications

With Microsoft VPN on the FTB platforms, or the ability to install and configure any VPN client solution defined by your IT department on it, secure communications are now within your reach.



3G/LTE mobility

Get connected wherever you are: choose any Windows-supported 3G/LTE USB dongle and connect to your wireless service provider.



Remote control

Use remote assistance to troubleshoot units in the field, trigger tests remotely, or help a technician with a problem. Working without it is hard to imagine.



Instant messaging

Because our platforms are Windows-based, they can provide some functions just like PCs. You can even use chat apps to quickly communicate with your team members (Skype comes preinstalled on the FTB-4 Pro).



EXFO | Connect

EXFO CONNECT MAKES YOUR DATA MEAN BUSINESS

EXFO Connect completely redefines integrated testing with its cloud-hosted solution. Equipped with a powerful database and application technologies, EXFO Connect provides an automated, secure environment that links together your EXFO test instruments, and centralizes captured data across your organization.

Test Equipment Manager

EXFO Connect's Test Equipment Manager is an automated application that centralizes the management of all EXFO test instruments. It is a repository for software loads, licenses and platform profiles to help managers handle constant demands for software updates. It keeps track of equipment and ensures field technicians are equipped with up-to-date capabilities.




Test Data Manager

EXFO Connect's Test Data Manager is an automated application that provides a secure and centralized environment in which test data is collected, archived and referenced for future use. With test results at their fingertips, managers can create birth certificates, generate reports and set benchmarks.

FTB Anywhere™: Floating Test Licenses

FTB Anywhere enables the sharing of test licenses. It is a feature of the award-winning FTB platform ecosystem. FTB Anywhere enables network operators to purchase a certain number of cloud-hosted licenses that can be shared instantly with their technicians, wherever they are.



DESIGNED FOR HIGH-SPEED AND MULTISERVICE

- | | | |
|---------------------------|--------------------------|------------------------------------|
| 1 Power on/off | 7 Stylus | 13 Module screws |
| 2 Battery LED | 8 Speaker | 14 Kensington security lock slot |
| 3 Switch application | 9 USB 2.0 port | 15 1 GigE port |
| 4 Keyboard/screen capture | 10 Display port | 16 USB 3.0 port |
| 5 Battery compartment | 11 Mic/Headset jack | 17 Power meter and VFL |
| 6 Back stand | 12 Internal power supply | 18 Four (4) slots to house modules |



EXFO

TECHNICAL SPECIFICATIONS ^a

Display	Touchscreen, color, 1280 × 800 TFT 256 mm (10.1 in)
Interfaces	RJ45 LAN 10/100/1000 Mbit/s Two USB 2.0 ports One USB 3.0 port Display port 3.5 mm headset/microphone port
Storage (internal flash memory)	128 GB
Battery (not included)	Two rechargeable Li-ion smart batteries (optional)
Power supply	AC input: ~ 100 – 240 V; 50/60 Hz; 5.2 – 1.9 A
Computer	Quad Core processor / 4 GB RAM / Windows 10

GENERAL SPECIFICATIONS

Size (H × W × D)	199 mm × 333 mm × 170 mm (7 ¹³ / ₁₆ in × 13 ¹ / ₈ in × 6 ¹¹ / ₁₆ in)
Temperature Operating Storage ^b	0 °C to 40 °C (32 °F to 104 °F) –40 °C to 60 °C (–40 °F to 140 °F)
Weight ^c	4.6 kg (10 lb)

BUILT-IN POWER METER SPECIFICATIONS (GeX) (OPTIONAL) ^d

Calibrated wavelengths (nm)	850, 1300, 1310, 1490, 1550, 1625, 1650
Optional CWDM calibrated wavelengths (nm)	1270, 1290, 1310, 1330, 1350, 1370, 1390, 1410, 1430, 1450, 1470, 1490, 1510, 1530, 1550, 1570, 1590, 1610, 1383, 1625
Power range (dBm) ^e	27 to –50
Uncertainty (%) ^{e, f}	±5 % ± 10 nW
Display resolution (dB)	0.01 = max to –40 dBm 0.1 = –40 dBm to –50 dBm

VISUAL FAULT LOCATOR (VFL) (OPTIONAL)

Laser, 650 nm ± 10 nm
CW/Modulate 1 Hz
Typical P _{out} in 62.5/125 µm: –1.5 dBm (0.7 mW)
Laser safety: class 2

Notes

- a. All specifications valid at 23 °C (73 °F).
b. Not including internal batteries. Battery storage temperatures: –20 °C to 60 °C (–4 °F to 140 °F) for shipping, and –20 °C to 45 °C (–4 °F to 113 °F) for long-term storage.
c. Platform without batteries or modules.
d. At 23 °C ± 1 °C, 1550 nm and FC connector. With modules in idle mode. Battery-operated after warm-up.
e. Typical.
f. At calibration conditions.

LASER SAFETY



The test modules that you use with your unit may have different laser classes. Refer to the module's documentation for exact information.

EXFO

ORDERING INFORMATION

FTB-4-Pro-XX-XX-XX-XX-XX-XX-XX-XX-XX

Model

FTB-4-Pro = Modular platform

Display

S1 = Standard display

S2 = Enhanced display for outdoor use

Memory

128G = 128 GB internal memory (flash)

Batteries

00 = without batteries

BTY = with batteries

WiFi/Bluetooth Option

00 = Without RF option enabled

RF = With RF option/capability (WiFi and Bluetooth)

NRF = Without RF hardware components^a**Power Meter/VFL**

00 = Without power meter

VPM2X = VFL platform; PM; GeX detector

VPM2X-CWDM = VFL platform; PM; GeX detector;
CWDM wavelengths calibrated**Connector Adapter**^b

FOA-12 = Biconic

FOA-14 = NEC D4: PC, SPC, UPC

FOA-16 = SMA/905, SMA-906

FOA-22 = FC/PC, FC/SPC, FC/UPC, FC/APC

FOA-28 = DIN 47256, DIN 47256/APC

FOA-32 = ST: ST/PC, ST/SPC, ST/UPC

FOA-54B = SC: SC/PC, SC/SPC, SC/UPC, SC/APC

FOA-78 = Radial EC

FOA-96B = E-2000 E-2000/APC

FOA-98 = LC

FOA-99 = MU

Software Option

00 = Without any software option

IPT = Ping and traceroute functionalities

EXpert-VolP = RTP-based call testing software application, including
packet loss analysis, jitter measurement and complete
voice quality metricsEXpert-IP = IP/Ethernet test suite, with tests including FTP performance,
HTTP availability, VLAN scan, LAN discovery, ping, traceroute
and IP/Ethernet port statistics (license for a single platform)

EXpert-IPTV = IPTV test suite

EXpert-TPP-Bundle = Triple-play bundle for voice, video and data testing;
includes EXpert IP Test Tools, EXpert IPTV Test
Tools, EXpert VoIP Test Tools and EXpert SIPEXpert-SIP = SIP call-signaling support^cEXpert-SCCP = SCCP call-signaling support^cEXpert-H.323 = H.323 call-signaling support^cEXpert-H.248 = H.248/Megaco call-signaling support^cFR2-PL = FastReporter 2 Software
Fiber characterization packageFR2-PL-LB = FastReporter 2 Software
Fiber characterization package and iOLM Loopback mode**Inspection Probe Base Tips**^d

APC = Includes FIPT-400-U25MA and FIPT-400-SC-APC

UPC = Includes FIPT-400-U25M and FIPT-400-FC-SC

Inspection Probe Models

00 = Without inspection probe

FP410B = Digital video inspection probe^e
Triple magnificationFP420B = Analysis digital video inspection probe^e
Automated pass/fail analysis
Triple magnification

Autocentering

FP425B = Wireless digital video inspection probe^{e, f}
Automated pass/fail analysis
Triple magnification

Autocentering

FP430B = Automated analysis digital video inspection probe^e
Automated focus
Automated pass/fail analysis

Triple magnification

Autocentering

FP435B = Wireless analysis digital video inspection probe^{e, f}
Automated focus
Automated pass/fail analysis

Triple magnification

Autocentering

Example: FTB-4-PRO-S1-128G-RF-VPM2X-FOA-54B-FP420B-APC-EXPERT-IP

Notes

a. Only available with S1 standard display.

b. Available if power meter is selected.

c. Available if EXpert VoIP selected.

d. Available if inspection probe is selected.

e. Includes ConnectorMax2 software.

f. Requires RF capability (WiFi/Bluetooth option).

EXFO Headquarters > Tel.: +1 418 683-0211 | Toll-free: +1 800 663-3936 (USA and Canada) | Fax: +1 418 683-2170 | info@EXFO.com | www.EXFO.comEXFO serves over 2000 customers in more than 100 countries. To find your local office contact details, please go to www.EXFO.com/contact.EXFO is certified ISO 9001 and attests to the quality of these products. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.For the most recent version of this spec sheet, please go to www.EXFO.com/specs.

In case of discrepancy, the web version takes precedence over any printed literature.