

ACTIVE DIFFERENTIAL PROBES SERIES 8000

The new TT-SI 8050 active differential probes allow safe, accurate measurements between two voltage points where neither point is referenced to ground. These probes are perfect designed for a wide variety of measurements up to 200MHz and are compatible with oscilloscopes from all major manufacturers.



	TT-SI 8050	TT-SI 8051	TT-SI 8052
Order Number	15402	15403	15404
Bandwidth	70MHz	100MHz	200MHz
Attenuation	x50 / x500		
DC-Accuracy	±2%		
Max. Input Voltage Differential Mode	±150V (DC + AC peak) @ x50 ±1500V (DC + AC peak) @ x500		
Max. Input Voltage Common Mode	±1500V (DC + peak AC)		
Maximum Input Voltage (each side to ground)	600Vrms CAT III 1000Vrms CAT II		
Safety Standard	IEC1010-031:2015		
Supplied Accessories	2 x Test Leads with insulated 4mm Banana Plugs (red & black) 2 x Grabber (red & black), 2 x Pincer (red & black) 2 x Alligator Clips (red & black), 1 x Insulated BNC Cable, 100cm 1 x USB power lead, 1 x Mains Adapter 220V EU Version		

Technical data subject to change

TESTEC

(ES) Equipements Scientifiques SA - Département Tests Energie Mesures - 127 rue de Buzenval BP 26 - 92380 Garches
Tél. 01 47 95 99 45 - Fax. 01 47 01 16 22 - e-mail: tem@es-france.com - Site Web: www.es-france.com