

WA-5000 Wavelength Analyzer

OPTICAL SPECTRUM ANALYZER



Fast and accurate optical spectrum analyzer, designed for production floor needs.

KEY FEATURES

Wavelength range:

- › O-band model: 1260-1360 nm
- › C-band: 1527-1567 nm

High speed sweeping in 500 ms (O-band)

Hardware resolution bandwidth = 250 pm

Software resolution bandwidth = 20-100 pm

Wavelength repeatability ± 10 pm

No mechanical life limitation

Long operation durability

EXFO

SPECIFICATIONS

Wavelength Analyzer	WA-5000-O	WA-5000-C
Wavelength range (nm)	1260 to 1360	1527 to 1567
Software resolution bandwidth (pm)	20 to 100	20 to 100
Absolute wavelength accuracy (pm)	±50	±40
Wavelength repeatability (pm)	±10	±10
Dynamic range (dBm)	−45 to 15	−50 to 15
Absolute power uncertainty (dB)	±0.8	±0.5
Maximum input power (dBm)	30	15
Power repeatability (dB)	±0.15	±0.1
Relative power accuracy (dB)	±0.5	±0.4
SMSR measurement range excluding PDL (dB)	<45	n/a
SMSR accuracy (dB)	≤ ±1.0 (SMSR ≤ 40 dB); ≤ ±1.5 (SMSR > 40 dB)	
PDL (dB)	<0.3	0.3
Noise floor (dBm)	−55	−55
Return loss (dB)	>30	>40
Sweep time (ms)	<500	<900
Connector type	FC/PC (9/125 μm)	
Weight (kg)	<10	

ORDERING INFORMATION

WA-5000-XX

Model

- = O-band optical spectrum analyzer
- = C-band optical spectrum analyzer

EXFO headquarters

EXFO is certified ISO 9001 and attests to the quality of these products. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.