FARMPRO

The original pocket sized grain moisture meter where the grain is ground and compressed in one operation. Compression,grinding and automatic temperature compensation is the key to the most accurate reading of water content in grain and seeds.

FARMPRO

MOISTURE ANALYZERS

FOR GRAIN AND SEEDS

THE PORTABLE GRAIN MOISTURE METER WITH BUILT-IN GRINDER

1







ES France - Département Bio-Tests & Industries - 127 rue de Buzenval BP 26 - 92380 Garches Tél. 01 47 95 99 90 - Fax. 01 47 01 16 22 - e-mail: bio@es-france.com - Site Web: www.es-france.com

MOISTURE ANALYZERS

FOR GRAIN **AND SEEDS**



FARMPRO

Additional features:

- Digital readout with accuracy to one decimal point
- Combined grinding and compression of sample
- Built-in measuring cups
- Automatic temperature compensation
- Grinder made of hardened galvanized steel
- Casing in shockproof ABS plastic
- Automatic calculation of average value
- Individual calibration for all grain types
- Can be updated with new moisture scales
- Supplied in shockproof transport case
- 2 year guarantee

The Farmpro Moisture Meter: Simple to use in four easy steps:



- by pressing the ON/TEST button.
- Use the arrow keys to select grain type.
- Turn on the tester Pour the sample into the grinder. The sample size is measured out in the built-in measuring cup.



Grind the sample.



Press the ON/TEST button and read the moisture content directly from the display.

TECHNICAL SPECIFICATIONS

- Measuring range (Moisture): 5 to 50% depending on crop type
- Operating range (Temperature): 0 to 50 °C
- Resolution: 0.1% moisture
- Temperature compensation: Automatic
- Weight including suitcase: 1.9 kg.

- Dimension: 21x7,5x7,5 cm
- Battery: 9 V Alkaline
- Display: 2 line LCD
- Accuracy: Better than +/- 0.25% in normal moisture range when using average and calibration adjustmentst



ES France - Département Bio-Tests & Industries - 127 rue de Buzenval BP 26 - 92380 Garches Tél. 01 47 95 99 90 - Fax. 01 47 01 16 22 - e-mail: bio@es-france.com - Site Web: www.es-france.com