



DIAL BORE GAUGE


- Dial indication with 10 microm resolution
- Solid construction with depth up to 2000mm Measuring range up to 1500mm)
- Calibration certificate included (ISO17025 (Ilac MRA))



6-10 mm



10-18 mm
18-50 mm



over 50 mm



Item No	Range	Resolution	Depth	Accuracy	Calibration
	mm	mm	mm	µm	ISO17025
131010100	6-10	0,01	45	±8	+
131018100	10-18		45	±8	+
131050100	18-50		135	±12	+
131050111			500	±12	+
131050122			1000	±12	+
131050144			2000	±12	+
131160100	50-160		200	±15	+
131160111			500	±15	+
131160122			1000	±15	+
131160144			2000	±15	+
131250100	160-250		200	±15	+
131250111			500	±15	+
131250122			1000	±15	+
131250144			2000	±15	+
131450100	250-450		200	±22	+
131450111			500	±22	+
131450122			1000	±22	+
131450144			2000	±22	+
131800100	400-800		250	±30	+
131800111			500	±30	+
131800122			1000	±30	+
131800144			2000	±30	+
131900100	700-1000		400	±30	+
131900122			1000	±30	+
131900144			2000	±30	+
	WIDE RANGE BORE GAUGES				
131110100	10-100	0,01	45	±15	+
131220100	20-200		200	±15	+
131224100	50-250		200	±15	+
131225100	18-250		150	±20	+
131951100	130-1500		500	±25	+



up to 1500mm