

COMMON MODE CHOKE/EMI , RFI FILTERS








- Vertical Series
- Rated Inductance : 0.2 ~ 47
- Rated Current : 0.3 ~ 6A
- Dielectric strength : 1500Vrms
- Rated Voltage 250V AC

Model No.	I RMS (Amps)	OCL(mH±30%)	MAX DCR(mΩ)
UT34873	6	0.2	20
UT34874	3.6	0.4	45
UT34875	2.5	0.6	75
UT34341	2.5	1	55
UT34342	2.5	2	80
UT34850	2	3.9	120
UT34396	1.2	6.8	280
UT34876	0.7	10	660
UT34877	0.6	15	840
UT34395	0.5	18	1000
UT34367	0.5	27	1100
UT34878	0.4	39	2000
UT34879	0.3	47	2200

ELECTRICAL SPECIFICATION @25°C

* For RoHS compliant products, a.)The Ordering Code: TG-Model No. ex. TG-UT34850
b.) Solder : Sn/Cu; c.)Date Code suffix to "G" (xxxxG)

DIMENSIONS & SCHEMATICS



UNIT : mm

*Specifications are subject to change without prior notice.

DATA SHEET 07-34 JAN./15
1 OF 1



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C