

Aranet RSSI sensor



- ① Radio signal strength is measured at the touch of a button
- ② Saves time during the installation process
- ③ Convenient for practical site survey



Designed to help IoT system deployers to plan and install the Aranet wireless monitoring solution in desired location.

Aranet RSSI sensor

Received Signal Strength Indicator of the Aranet radio

TDSPTT02 (EU)

TDSPTTU2 (NA)

TDSPTTR2 (RU)

Sensor performance

Minimum detectable value	-130 dBm
Resolution	1 dBm

Radio parameters

Line of sight range	3 km (1.9 mi)
Supported ISM bands	EU868, NA915
Transmitter power	14 dBm
Data protection	XXTEA encryption
Compatible base stations	Aranet PRO

General

Ingress Protection code	IP42
Maximum operating temperature range	-40 °C to 60 °C (-40 °F to 140 °F)
Dimensions	Ø 35 x 120 mm (Ø 1.4 x 4.7 in)
Weight ¹	69 g (2.1 oz)
Enclosure material	ASA plastic
Included in the box	1 AA alkaline battery, polyester string

Compliance

CE	Conformité Européenne
IC	Innovation, Science and Economic Development Canada
FCC	Federal Communications Commission (USA)

¹ Weight with alkaline AA Fujitsu LR6G07 Premium battery.