

BAV19WS-BAV21WS SWITCHING DIODE



Features

- Fast Switching Speed
- Surface Mount Package Ideally Suited for Automatic Insertion
- For General Purpose Switching Applications
- High Conductance
- This is a Halogen Free Device
- “-A” is an AEC-Q101 qualified device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

Schematic & Pin Configuration



Mechanical Characteristics

- Case: SOD-323, Molded plastic
- Terminals: Plated leads solderable per MIL-STD-202, Method 208

Maximum Ratings@T_A=25°C unless otherwise specified





Characteristic	Symbol	BAV19WS	BAV20WS	BAV21WS	Unit
Marking Code		A8	T2	T3	
Non-Repetitive Peak Reverse Voltage	V _{RM}	120	200	250	V
Peak Repetitive Peak Reverse Voltage	V _{RRM}	100	150	200	V
Working Peak Reverse Voltage	V _{RWM}				
DC Blocking Voltage	V _R				
RMS Reverse Voltage	V _{R(RMS)}	71	106	141	
Average Rectified Output Current	I _O	200			mA
Forward continuous current	I _{FM}	400			mA
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method) @t=1.0ms @ t=1.0s	I _{FSM}	2.5 0.5			A
Power Dissipation	P _d	250			mW
Repetitive Peak Forward Current	I _{FRM}	625			mA
Typical Thermal Resistance Junction to Ambient	R _{θJA}	500			°C/W
Junction Temperature Range	T _J	150			°C
Storage Temperature Range	T _{STG}	-55 to +150			°C

- China - Germany - Korea - Singapore - United States •
- <http://www.smc-diodes.com> - sales@smc-diodes.com •

Electrical Characteristics@T_A=25°C unless otherwise specified

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage*	V _F	I _F =100mA I _F =200mA	-	0.95 1.06	1.00 1.25	V
Reverse Leakage Current*	I _R	V _R =100V V _R =150V V _R =200V	-	0.007	0.1	μA
Diode capacitance	C _T	V _R =0V, f=1.0MHz	-	1.2	5	pF
Reverse recovery time	t _{rr}	I _F = I _R =30mA, I _{rr} =0.1×I _R , R _L =100 Ω	-	-	50	ns

* Pulse width < 300 μs, duty cycle < 2%

Ratings and Characteristics Curves



- China - Germany - Korea - Singapore - United States •
- <http://www.smc-diodes.com> - sales@smc-diodes.com •

Ordering Information

Device	Package	Shipping
BAV19WS-BAV21WS	SOD-323	3000pcs / reel
BAV19WSTR-BAV21WSTR	SOD-323	3000pcs / reel


For information on tape and reel specifications, including part orientation and tape sizes, please refer to our tape and reel packaging specification.

Marking Diagram




A8 = Marking Code

Mechanical Dimensions SOD-323



SYMBOL	Millimeters		Inches	
	MIN.	MAX.	MIN.	MAX.
A	-	1.000	-	0.039
A1	0.000	0.100	0.000	0.004
A2	0.800	0.900	0.031	0.035
b	0.250	0.350	0.010	0.014
c	0.080	0.150	0.003	0.006
D	1.200	1.400	0.047	0.055
E	1.600	1.800	0.063	0.071
E1	2.500	2.700	0.098	0.106
L	0.475 REF.		0.019 REF.	
L1	0.250	0.400	0.010	0.016
θ	0°	8°	0°	8°

Carrier Tape Specification SOD-323



SYMBOL	Millimeters	
	Min.	Max.
B	2.85	2.95
C	1.20	1.30
d	1.40	1.60
E	1.65	1.85
F	3.40	3.60
P	3.90	4.10
P0	3.90	4.10
P1	1.90	2.10
W	7.90	8.30

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..