

Intel Celeron/i3/i5 15.6 inch Industrial Panel PC EM-PPC15S PRO



Product Feature:

- Support Intel® Celeron® i3/i5
- Up to DDR4 16GB RAM
- Fanless with low consumption
- Wide Temperature Operating: -20°C ~ 60°C
- IP65 of front panel
- 9~36V Wide Voltage Input

Ordering Information:

Model	Parameter	Configuration
EM-PPC15S1 PRO	CPU	Intel® i3 6100U, 2.3GHz
	Memory	Up to DDR4 16GB
	USB 3.0	4
	OS support	Windows® 7, Windows® 10, Linux
Model	Parameter	Configuration
EM-PPC15S2 PRO	CPU	Intel® i5 6200U, 2.3GHz
	Memory	Up to DDR4 16GB
	USB 3.0	4
	OS support	Windows® 7, Windows® 10, Linux
Model	Parameter	Configuration
EM-PPC15S3 PRO	CPU	Intel® i3 7100U, 2.4GHz
	Memory	Up to DDR4 16GB
	USB 3.0	4
	OS support	Windows® 7, Windows® 10, Linux
Model	Parameter	Configuration
EM-PPC15S4 PRO	CPU	Intel® i5 7200U, 2.5GHz
	Memory	Up to DDR4 16GB
	USB 3.0	4
	OS support	Windows® 7, Windows® 10, Linux

Model	EM-PPC15S PRO	
System Parameter	CPU	Intel® Celeron® 3855U 1.6GHz/3865U 1.8GHz Intel® i3 6100U 2.3GHz/7100U 2.4GHz Intel® i5 6200U 2.3GHz/7200U 2.5GHz
	Chipset	Intel® System on Chip
	RAM	Up to DDR4 16GB
	Storage	1 x mSATA
	I/O	2 x GbE RJ45 Intel i211, 4 x USB3.0
		2 x DB-9, RS-232/422/485 (Optional)
		4 x DB-9, RS-232
		1 x Audio Output
		2 x 8Ω 2W Power amplifier output (Optional)
		1 x HDMI, 1 x VGA
	Expansion Slot	Mini-PCIE x1 On-board SIM, Support 3G/4G or WiFi/BT (The module is optional)
	OS	Windows 7, Windows 10, Linux
Display	Size	15.6" TFT-LCD 16 : 9
	Resolution	1920 x 1080
	Display Color	16.7M
	Brightness	300cd/m²
	Visual Angle	160/160(H/V)
	Backlight Life	50,000h
Touch Panel	Type	Capacitive touch
	Transmittance	88%
Power	DC	9-36V DC IN
Material	Material	Aluminium alloy
	Installation Method	VESA 75 / VESA 100 / Embedded
	IP Code	IP65 of front panel
	Dimension	384.3 x 243.9 x 74 mm
	Weight	3.1Kg
Reliability	Operate Temperature	-20°C to 60°C
	Storage Temperature	-30°C to 70°C
	Humidity	10~90%@40°C, Non-Condensing

Product specifications, pictures and other information are for reference only.
The appearance is subject to the material object. This instruction is subject to change without notice.

