

▶ PORTABLE SF₆ VACUUM CAR110-01

DESCRIPTION

- **Dry vacuum pump** in a portable module
- Compact and **easily transportable**
- All connections are **molecular sealed**
- In combination with CAR109-02 Portable SF₆ Compressor allows **Recovery from the equipment up to a pressure of less than 1 mbar abs** (compliant with CEI EN62271-4) and Storage in a cylinder in a liquid state



TECHNICAL SPECIFICATIONS

⚙️ DIMENSIONS: Length: 500 mm - Width: 290 mm - Height: 250 mm

⚙️ WEIGHT: 19 kg

⚙️ OPERATING VOLTAGE: 220 - 240V 50/60 Hz

STANDARD EQUIPMENTS

Dry vacuum pump: Nominal flow rate: 3 m³/h (50 Hz);
3,6 m³/h (60 Hz) - Final pressure: <1 mbar

Protection Solenoid valve

Precision digital vacuumeter (0-100 mbar)

Precision digital vacuumeter display

Folding handles

2x 5m rubber hoses DN8 with coupling valves DN8

Operating manual

▶ **PORTABLE SF₆ VACUUM**
CAR110-01

CERTIFICATES ISSUED

- 📄 Plant Helium Leak Test Certificate
(UNI EN ISO 9712 - SNT TC1A)

OPTIONAL ACCESSORIES

- ☆ **PKG101-02** Alluminium transport case for CAR110-01
- ☆ **TBS101-02**: 2mt Rubber hose DN8 with DN8 female valves
- ☆ **TBS101-03**: 5mt Rubber hose DN8 with DN8 female valves
- ☆ **TBS101-04**: 10mt Rubber hose DN8 with DN8 female valves
- ☆ **TBS106-01**: Storage hose connection
- ☆ **VAL102-01**: Adapters kit DN8
- ☆ **ACC101-04**: Inlet Particle Filter