

▶ PORTABLE AIR VACUUM CAR111-01

DESCRIPTION

- **15 m³/h vacuum pump**
- Ideal for: **Air and Nitrogen evacuation**
- Compact and **easily transportable**
- All connections are **molecular sealed**
- **Portable line:** same as CAR110-01 Portable SF₆ Vacuum and CAR109-02 Portable SF₆ Compressor and ACC101-01 SF₆ Integrated Filter



TECHNICAL SPECIFICATIONS

⚙️ DIMENSIONS: Length: 510 mm - Width: 350 mm - Height: 280 mm

⚙️ WEIGHT: 22 kg

⚙️ OPERATING VOLTAGE: 220 - 240V 50/60 Hz

STANDARD EQUIPMENTS

Vacuum pump: Nominal flow rate: 15 m³/h (50 Hz); 18 m³/h (60 Hz) - Final pressure: <1 mbar

Solenoid valve DN8

Precision digital vacuumeter (0-100 mbar)

Precision digital vacuumeter display

5m DN8 rubber hose with coupling valves DN8

Operating manual

► **PORTABLE AIR VACUUM**
CAR111-01

CERTIFICATES ISSUED

- 📄 Plant Helium Leak Test Certificate
(UNI EN ISO 9712 - SNT TC1A)

OPTIONAL ACCESSORIES

- ☆ **PKG101-01**: Alluminium transport case for CAR111-01
- ☆ **TBS101-02**: 2mt Rubber hose DN8 with DN8 female coupling valves
- ☆ **TBS101-03**: 5mt Rubber hose DN8 with DN8 female coupling valves
- ☆ **TBS101-04**: 10mt Rubber hose DN8 with DN8 female coupling valves
- ☆ **TBS106-01**: Storage hose connection
- ☆ **VAL102-01**: Adapters kit DN8
- ☆ **ACC101-04**: Inlet Particle Filter