



GT OTC325 32" Curved Touchmonitor (C-type)

With C Type format, 2K Resolution, vibrant colors, GT Curved Touch Monitors, allow for more impressive visual contents and captivating play. Sleek appearance, engaging visuals and accurate PCAP multi-touch experience let excited players immerse into the gaming atmosphere and enjoyment. It's an ideal touch solution widely used in the gaming, casino and sports betting.

Features & Benefits

- Unique Industrial-grade Design
- Curved 1500R Comfortable Viewing Experience
- Accurate PCAP Multi-touch Technology
- 2K Resolution
- VESA Mounting, Portrait or Landscape
- Edge-to-edge Design, Easy to Clean
- DVI, HDMI, DP Interface with External OSD



Applications

- Gaming
- Retail
- Amusement Industry

SPECIFICATIONS

Name	32" Curved Touchmonitor (C-type)
Model	OTC325
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	697.34×392.26mm
Native Resolution	2560×1440@144Hz
Response Time (Typ.)	20ms
Display Colors	16.7M
Luminance (Typ.)	250nits; with P-Cap 212nits
Contrast Ratio (Typ.)	2500:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°
	Vertical (up/down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (P-Cap)
Surface Treatment	Tempered or Chemically Strengthened
Thickness(Total)	4.5±0.5mm
Light Transmission	≥83%
Response Time	8ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Black
Radius	R1500
Mounting Options	Back mounting: 400×360 mm (see drawing for details)
Outline Dimensions (W×H×D)	795.30mm × 490.20mm× 96.40mm
Power Supply	Input Voltage Range: +24VDC ± 5%
On Screen Display (OSD)	Control (remote): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 60W
Operating Altitude	≤3000m
System support	Win7 or later, Linux 4.4 or later

Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	HDMI, DVI, DP, USB (Type B)
Accessories	Optional
Carton Box Dimensions (1 unit in one carton)	905mm (L) × 215mm (W) × 630mm (H)
Weight	Net: 15.1kg Gross: 19.3kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE , FCC

Ordering Information		
Model	Part Number	Description
OTC325-RC5000-UD2U00-1.0	110302775R	32" "C type", 2K, 16:9, 250nits, P-Cap, USB, HDMI/DVI/DP

Optional Accessories		
Model	Part Number	Description
DVI Cable	130300720R	DVI Cable, 1500mm, 18+1pin, male to male
DP Cable	130300932R	DP Cable, 1500mm, 20pin to 20pin, male to male, black
HDMI Cable	130300881R	1500mm
USB Cable	130300224R	USB Cable, 1500mm, male to male
Adaptor	130104171R	G99-KEP150M-N001 Input:100-240V(VAC)- Output :24(VDC)-6.25A-150W-4PIN
Power Cable		1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>