

GT RTL226 21.5" Rear Mount Touchmonitor



GT RTL226 Commercial-grade 21.5" rear mount touchmonitor delivers a better visual experience and more realistic and accurate touch experience.

With the unique design of widescreen and narrow border, RTL226 allows more content on the screen than standard with an even smaller and artistic outline. GT RTL226 features multiple interfaces and flexible mounting, ease of connection to various devices, and installation into the cabinet. It's an ideal touch solution for retail, gaming, kiosk, self-service, finance, transport, conference, education, and healthcare.

Features & Benefits

- Accurate PCAP 10-point multitouch technology
- Edge-to-edge true-flat design with low maintenance
- Flexible mounting, Support VESA and all four-side bracket
- HDMI,VGA,DP interface
- Anti-scratches
- Easy installation to the cabinet
- 3 Years Warranty



Applications

- | | | | | |
|----------|---------------|------------------|-----------|----------------|
| ■ Retail | ■ Corporation | ■ Medical | ■ Banking | ■ Self-service |
| ■ Gaming | ■ Kiosk | ■ Transportation | | |

SPECIFICATIONS

Name	21.5" Rear Mount Touchmonitor
Model	RTL226-LRPCZ04-UHPDA
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD with LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	476.64 × 268.11mm
Native Resolution	1920 × 1080@60Hz
Response Time (Typ.)	18ms
Display Colors	16.7million
Luminance (Typ.)	250nits; with PCAP 210nits
Contrast Ratio (Typ.)	3000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°
	Vertical (up/down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (PCAP)
Surface Treatment	Tempered or Chemically Strengthened
	Optional: Anti-glare
Active Area(W x H)	476.4 × 268.1 ± 0.3mm
Thickness(Total)	3.3 ± 0.3mm
Light Transmission	≥83%
Response Time	8ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Black
Mounting Options	VESA: 100 × 100 mm; Rear Mounting; Side Mounting
Outline Dimensions (W×H×D)	516mm × 311mm × 37.9mm
Power Supply	External Adapter: 100-240V AC, 50-60 Hz
	Input Voltage Range: +12VDC ± 5%
On Screen Display (OSD)	Control (External): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 20W
Speaker	NA
Webcam	NA

Operating Altitude	≤3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, HDMI, DP, USB (Type B), Mini Din(External OSD)
Accessories	Cables: VGA × 1, USB × 1, 1.5m Length; Bracket × 2; OSD Remote
Carton Box Dimensions (2 units in one carton)	630mm (L) × 250mm (W) × 430mm (H)
Weight	Net: 14.62kg Gross: 5.56kg
MTBF	50,000 hours demonstrated
Agency Approvals	CCC, CE , FCC, UL
Warranty	3 years

Ordering Information		
Model	Part Number	Description
RTL226-LRPCZ04-UHPDA		21.5", 16:9, 250nits, PCAP, USB, VGA & HDMI & DP, Black
RTL226-LRPCZ04A-UHPDA		21.5", 16:9, 250nits, PCAP, USB, VGA & HDMI & DP, Black Anti-glare

Contact sales for other options

Optional Accessories		
Model	Part Number	Description
Adaptor	130104158R	12V/5A, DC Cable: 1200mm, DC Jet ø2.1mm
	130300338R	UK
Power Cord	130300339R	EU 1500mm
	130300340R	US
HDMI Cord	130300881R	1500mm
DP Cord	130300932R	1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>