

GT OTL22W 21.5" Closed Frame Touchmonitor



With PCAP touch technology, GT OTL22W Closed frame touch monitor inherits the advantages of traditional products, such as high reliability, high durability, high clarity, and scratch resistance, also can provide dustproof, waterproof, vandal-proof, anti-glare optional. The LED backlight module provides a slim look, longer life, and lower power consumption for the touch monitor. It's the best choice for various public applications such as self-service, kiosks, interactive digital signage, etc.

Features & Benefits

- Accurate PCAP Multitouch Technology
- Sleek Appearance
- Anti-scratch Touchscreen
- Easy Integration and Low Maintenance
- VGA, DVI
- Commercial-grade Continuous (24/7) Use
- Optional Anti-glare
- VESA Mounting/ Wall Mounting



Applications

- | | | | | |
|----------|---------------|------------------|-----------|----------------|
| ■ Retail | ■ Corporation | ■ Medical | ■ Banking | ■ Self-service |
| ■ Gaming | ■ Kiosk | ■ Transportation | | |

SPECIFICATIONS

Name	21.5 Inch Closed Frame Touch Monitor
Model	OTL22W
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD with LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	476.64 × 268.11mm
Native Resolution	1920 × 1080@60Hz
Response Time (Typ.)	18ms
Display Colors	16.7million
Luminance (Typ.)	250nits; with PCAP 210nits
Contrast Ratio (Typ.)	3000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°
	Vertical (up/down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (PCAP)
Surface Treatment	Strengthened
	Optional: Anti-glare
Active Area(W x H)	476.4 × 268.1 ± 0.3mm
Thickness(Total)	2.4 ± 0.3mm
Light Transmission	≥83%
Response Time	8ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Black
Mounting Options	VESA: 75 × 75 mm 100 × 100 mm
Outline Dimensions (W×H×D)	529.5mm × 316.5mm × 40.0mm
Power Supply	External Adapter: 100-240V AC, 50-60 Hz
	Input Voltage Range: +12VDC ± 5%
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 20W
Speaker	NA
Webcam	NA

Operating Altitude	≅ 3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, DVI, USB (Type B)
Accessories	Cables: VGA × 1, USB × 1, 1.5m Length
Carton Box Dimensions	660mm (L) × 460mm (W) × 180mm (H)
Weight	Net: 5.8kg Gross: 8.1kg
MTBF	50,000 hours demonstrated
Agency Approvals	CCC, CE , FCC
Warranty	3 years

Ordering Information		
Model	Part Number	Description
OTL22W-RPCZ03-UCD	110301811R	21.5", 16:9, 250nits, PCAP, USB, VGA & DVI, Black

Contact sales for other options

Optional Accessories		
Model	Part Number	Description
Adaptor	130102978R	12V/4.17A, DC Cable: 1500mm, DC Jet Ø2.5mm
DVI Cord	130300720R	1500mm
	130300338R	UK
Power Cord	130300339R	EU 1500mm
	130300340R	US

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>