



GT OTL323 32" Hight Bright Touchmonitor

OTL323 is a touchmonitor using industrial grade LED, with 1200nits luminance, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or monitor, OTL323 industrial-grade high performance and professional design is better suited for outdoor application even under strong light.

Features & Benefits

- Accurate PCAP Multitouch Technology
- Sleek Appearance
- Hight Bright luminance 1200nits
- External VESA Mounting
- Easy Integration and Low Maintenance
- HDMI, VGA, DVI, DP Interface
- Commercial-grade Continuous (24/7) Use
- Anti-glare Optional



Applications

- | | | | | |
|----------|-----------------|------------------|-----------|----------------|
| ■ Retail | ■ Corporation | ■ Medical | ■ Banking | ■ Self-service |
| ■ Gaming | ■ Outdoor Kiosk | ■ Transportation | | |

SPECIFICATIONS

Name	32” Hight Bright Touchmonitor	
Model	OTL323	
LCD Panel Parameters		
Display Technology	Active Matrix TFT-LCD with LED Backlight	
Aspect Ratio	16:9	
Active Area (W x H)	698.40 x 392.85 mm	
Native Resolution	1920 x 1080	
Response Time(Typ.)	8ms	
Display Colors	16.7M	
Luminance(Typ.)	1200nits, TNI: 90°C	
Contrast Ratio (Typ.)	1200:1	
Viewing Angle(cr≥10)	Horizontal(left/right) Typ.	178°(89°/89°)
	Vertical(up/down) Typ.	178°(89°/89°)
Touch Screen Parameters		
Touch Technology	Projected Capacitive Touch (PCAP)	
Surface Treatment	Strengthened	
	Optional: Anti-glare	
Active Area(W x H)	699.2 ×393.7±0.5mm	
Thickness(Total)	7.3±0.3mm	
Light Transmission	≥83%	
Response Time	8-10ms	
Touch Screen Interface	USB	
Touch Point	10	
Overall Parameters		
Case/Bezel Color	Black	
Mounting Options	Side Mount; VESA 100 × 100mm	
Outline Dimensions (W×H×D)	769.2×463.7×80.0mm	
Power Supply	110-240V AC	
Light sensor	yes	
On Screen Display (OSD)	Control(back): Power, Auto, Up, Down, Menu	
Power Consumption	MAX :80W	
Speaker	NA	
Webcam	NA	

Operating Altitude	≤ 3000m
Temperature Range	Operating: -20°C to 40°C, Humidity 20% to 80%
Humidity (Non Condensing)	Operating: 40°C to 60°C, Humidity 20% to 40%
	Storage: -20°C to 40°C, Humidity 10% to 90%;
	Storage: 40°C to 60°C, Humidity 10% to 40%
I/O	VGA, DVI, DP, HDMI, USB(Type B)
Accessories	Cable: 1.5m USB cable × 1, 1.5m VGA cable × 1
Carton Box Dimensions	900.00mm × 210.00mm × 620.00mm
Weight	TBD
MTBF	50,000 hours demonstrated
Agency Approvals	Rohs
Warranty	3 years (LCD panel & Touch Screen : 1 year)

Ordering Information		
Model	Part Number	Description
OTL323-RC8000-UDA2L0-1.0	110302995R	32", 16:9, 1200nits, PCAP, High brightness
OTL323-RC80A0-UDA2L0-1.0	110303313R	32", 16:9, 1200nits, PCAP, High brightness, Anti-glare

Optional Accessories		
Model	Part Number	Description
Power Cord	130300338R	UK 1500mm
	130300339R	EU 1500mm
	130300340R	US 1500mm
DVI Cord	130300720R	1500mm
HDMI Cord	130300881R	1500mm
DP Cord	130300932R	1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>