

To Measure Is To Know

# WatchDog® 3000 Series Wireless Weather Station



\*3240MU Model Shown Above

#### Item# **Modem Type** 3240DR No Modem 3240DE Station Pup, 868Mhz Wi-Fi 3240WF LTE-M 3240MU 3240CE LTE CAT-4

## How well do you trust your weather app?

Gather real-time, site-specific data to adjust your field activities for the most profitable growing decisions.

Rainfall

#### **MEASURES**

- **Temperature Relative Humidity** 
  - **Optional Sensor** Wind Speed/Direction

#### **FEATURES**

- Configure your station and view current conditions via the free WatchDog<sup>®</sup> Mobile App
- Integrated solar power system
- Internal data logger. Holds 10 months of data at a 15-minute recording interval. Data can be transferred to a USB flash drive.
- Customizable plug-in sensors
- Simple installation. Mounts to a 1.25 inch mast U-bolts included



- View reports of current conditions or historical data from any location
- Receive alerts via automated phone call, text message, and/or email immediately when temperature crosses your selected threshold

#### **ACCESSORIES**

ltem #	Description
<u>3030</u>	SpecConnect Pro Subscription - WiFi
<u>3010EU</u>	SpecConnect Pro Subscription
3000	SpecConnect Initial Setup Fee
3070	Alerts Function for up to 4 Phone Numbers

### **SPECIFICATIONS**

Air Temperature	±0.54°F (-40° to 194°F); ±0.3°C (-40 to 90°C)
Relative Humidity	±2% @ 77°F (25°C); 0 to 100%
Rainfall	±2% at <2" (5 cm)/hr; 0.01" (0.25 mm) Resolution
Wind Speed / Direction	±2 mph (±3 km/h), ±5% / ±3°
External Sensor Ports	1 x 2.5mm stereo jack (0 to 3.0VDC analog input)
Operating Temperature Range	-22° to 130°F (-30° to 55°C)
<b>External Communication</b>	Cellular, USB, Bluetooth, RS232
Power Source	3.5W solar panel, rechargeable 6V/4.5AH SLA battery
Battery Life	14 days minimum with no solar power
Data Capacity	312 days at 15-minute intervals (30,000 records)
Dimensions	H x L x W: 12 x 19.5 x 11.25 in (30.5 x 49.5 x 28.6 cm)
	plus 7.25 in (18.4 cm) Antenna