


7706 All-in-One I/O Module

20-channel Differential Multiplexer w/Automatic CJC, 16 Digital Outputs, 2 Analog Outputs, a Counter/Totalizer, and Screw Terminals

Datasheet




KEITHLEY
A Tektronix Company

The 7706 plug-in module offers 20 channels of 2-pole or 10 channels of 4-pole multiplexer switching with automatic CJC, as well as two analog output channels, 16 digital outputs, and one event counter/totalizer. The event counter/totalizer can be used to monitor and control system components, such as fixtures, limit switches, pass/fail indicators, external voltage sources, loads, door closures, revolutions, etc., while performing mixed signal measurements. The 7706 is ideal for RTD, thermistor, and thermocouple temperature applications.

Key Features

- 20 channels of analog input (w/automatic CJC) for general-purpose measurements
- 16 channels of digital output
- 2 analog outputs (± 12 V, 5 mA)
- 300 V, 1 A capacity; 60 W, 125 VA maximum
- Configurable as two independent banks of multiplexers
- Relay closures stored in onboard memory



Specifications

Capabilities

Channels 1–20	Multiplex one of 20 2-pole or one of 10 4-pole signals into DMM.
Channels 21–22	16 Digital Outputs.
Channels 23–24	Analog Voltage Output (2).
Channels 25	Totalize Input.
Channels 21–25 are referenced to chassis ground.	

Inputs (Channels 1–20)

Maximum Signal Level (Channels 1–20)	300 V DC or rms, 1 A switched, 60 W, 125 VA maximum.
--------------------------------------	--

Safety Category	CAT 1
Contact Life (typ.)	>10 ⁹ operations at max. signal level; >10 ⁸ operations no load ¹ .
1. Minimum signal level 10 mV, 10 μ A.	

Contact Resistance	<1 Ω at end of contact life.
--------------------	-------------------------------------

Contact Potential	< ± 2 μ V typical per contact, 3 μ V max.
-------------------	---

Offset Current	<100 pA.
----------------	----------

Connector Type	Screw terminal, #22 AWG wire size.
----------------	------------------------------------

Isolation Between Any Two Terminals:	>10 ⁹ Ω , <100 pF.
--------------------------------------	--------------------------------------

Isolation Between Any Terminal and Earth:	>10 ⁹ Ω , <200 pF.
---	--------------------------------------

Cross Talk (10MHz, 50 Ω Load):	<–35 dB.
---------------------------------------	----------

Insertion Loss (50 Ω Source, 50 Ω Load)	<0.1 dB below 1 MHz. <3 dB below 2 MHz.
---	---

Common Mode Voltage:	300 V between any terminal and chassis.
----------------------	---

Digital Output (Channels 21 and 22)

V _{out} (L)	<0.8 V @ I _{out} = 400 mA.
----------------------	-------------------------------------

V _{out} (H)	>2.4 V @ I _{out} = 1 mA.
----------------------	-----------------------------------

V _{out} (H)Max.	<42 V with external open drain pull-up.
--------------------------	---

Write Speed	50/s.
-------------	-------

Analog Voltage Output (Channels 23 and 24)

DAC 1, 2	± 12 V @ 1 mA max, non-isolated, ± 10 V @ 5 mA max.
----------	---

Resolution	1 mV.
------------	-------

I _{out}	5 mA max.
------------------	-----------

Settling Time	1 ms to 0.01% of output.
---------------	--------------------------

Accuracy $\pm$ (% of output + mV)	1 year $\pm 5^\circ\text{C}$: 0.15% + 19 mV; 90 day $\pm 5^\circ\text{C}$: 0.1% + 19 mV; 24 hour $\pm 1^\circ\text{C}$: 0.04% + 19 mV.
-----------------------------------	---

Temperature Coefficient:	$\pm(0.015\% + 1 \text{ mV})/^\circ\text{C}$.
--------------------------	--

Write Speed	50/s.
-------------	-------

Totalize Input (Channel 25)

Maximum Count	232–1.
---------------	--------

Totalize Input	100 kHz (max), rising or falling edge, programmable.
----------------	--

Signal Level	1 Vp-p (min), 42 Vpk (max).
--------------	-----------------------------

Threshold	0 V or TTL, jumper selectable.
-----------	--------------------------------

Gate Input	TTL-Hi, TTL-Lo, or none.
------------	--------------------------

Count Reset	Manual or Read+Reset.
-------------	-----------------------

Read Speed	50/s.
------------	-------

General

20 Channels	20 channels of 2-pole relay input. All channels configurable to 4-pole.
-------------	---

Relay Type	Latching electromechanical.
------------	-----------------------------

Actuation Time	<3 ms.
----------------	--------

Environmental and Safety

Operating Environment: Specified for 0° to 50°C. Specified to 80% R.H. at 35°C.

Storage Environment: –25° to 65°C.

EMC: Conforms to European Union EMC Directive.

Safety: Conforms to European Union Low Voltage Directive

RoHS: Conforms to European Union RoHS Directive

Weight	0.5 kg (1.1 lbs).
--------	-------------------

Supplied Accessories

CC-92-1	Set of 20 Cable Ties
TL-23	Screwdriver

Available Services

7706-3Y-EW	1-year factory warranty extended to 3 years from date of shipment
------------	---

Ordering Information

7706	All-in-One I/O Module
Warranty	1 year

Tektronix

Contact Information:

Australia* 1 800 709 465
Austria 00800 2255 4835
Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
Belgium* 00800 2255 4835
Brazil +55 (11) 3759 7627
Canada 1 800 833 9200
Central East Europe / Baltics +41 52 675 3777
Central Europe / Greece +41 52 675 3777
Denmark +45 80 88 1401
Finland +41 52 675 3777
France* 00800 2255 4835
Germany* 00800 2255 4835
Hong Kong 400 820 5835
India 000 800 650 1835
Indonesia 007 803 601 5249
Italy 00800 2255 4835
Japan 81 (3) 6714 3010
Luxembourg +41 52 675 3777
Malaysia 1 800 22 55835
Mexico, Central/South America and Caribbean 52 (55) 56 04 50 90
Middle East, Asia, and North Africa +41 52 675 3777
The Netherlands* 00800 2255 4835
New Zealand 0800 800 238
Norway 800 16098
People's Republic of China 400 820 5835
Philippines 1 800 1601 0077
Poland +41 52 675 3777
Portugal 80 08 12370
Republic of Korea +82 2 6917 5000
Russia / CIS +7 (495) 6647564
Singapore 800 6011 473
South Africa +41 52 675 3777
Spain* 00800 2255 4835
Sweden* 00800 2255 4835
Switzerland* 00800 2255 4835
Taiwan 886 (2) 2656 6688
Thailand 1 800 011 931
United Kingdom / Ireland* 00800 2255 4835
USA 1 800 833 9200
Vietnam 12060128

* European toll-free number. If not accessible, call: +41 52 675 3777



Find more valuable resources at TEK.COM

Copyright © Tektronix. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.
041618.SBG 1KW-00000-0



ES France - Département Tests & Mesures - 127 rue de Buzenval BP 26 - 92380 Garches
Tél. 01 47 95 99 45 - Fax. 01 47 01 16 22 - e-mail: tem@es-france.com - Site Web: www.es-france.com