
IEEE-488 (GPIB) Accessories



Model 7006-*: Single-shielded GPIB cable terminated with one feed through style and one straight on IEEE-488 connector. The mating thumb screws are metric.

7006-1 1m (3.3 ft) **7006-2** 2m (6.6 ft)



Model 7007-*: Double-shielded premium GPIB cable. Each end is terminated with a feed through style metal housing for longest life and best performance. The mating thumb screws are metric.

| 7007-05 | 0.5m (1.6 ft) |
|---------|---------------|
| 7007-1 | 1m (3.3 ft) |
| 7007-2 | 2m (6.6 ft) |
| 7007-3 | 3m (10 ft) |
| 7007-4 | 4m (13.1 ft) |

For use with: IEEE-488 Interconnect



Model 7010 Shielded IEEE-to-IEEE Adapter: Provides additional clearance between IEEE-488 cable and rear panel, allowing easier access to switches, cables, and other connectors.

For use with: IEEE-488 Interconnect



Model 8530 Centronics Adapter: IEEE-488 to Centronics cable adapter. Connects to Model 2001/2002 IEEE-488 port and any Centronics compatible printer for direct data output.

Cable Length: 2m (6.6 ft).

For use with: 2001, 2002

GPIB accessories, shielded and unshielded

1.888.KEITHLEY (U.S. only)

www.keithlev.com

