



49 Inch "J type" Closed Frame Touch Monitor

OTJ495 is a Curved Touch Monitor, As GT's 5th generation PCAP touch monitor solution is ideal not only for gaming applications but also for those small and large interactive digital signage displays where fast, accurate and sensitive touch solution is required. These monitors are available if you want to attract customers to the latest, largest and most exciting gaming experience possible.

Features & Benefits

- Curved R1500, black closed-frame designs
- 10-touch PCAP for windows 7 or later, Linux 4.4 or later
- 4K resolution



USB Power
24V DC



Earphone DP HDMI DVI



Applications

- Gaming
- SLOT
- Casino

SPECIFICATIONS

Name	49 Inch "J type" Closed Frame Touch Monitor
Model	OTJ495
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	1073.78 × 604.00mm
Native Resolution	3840 × 2160@60Hz
Response Time (Typ.)	8ms
Display Colors	1.07B
Luminance (Typ.)	500nits; with PCAP 415nits
Contrast Ratio (Typ.)	1100:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°
	Vertical (up/down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (PCAP)
Surface Treatment	Tempered or Chemically Strengthened
Thickness(Total)	4.5 ± 0.5mm
Light Transmission	≥83%
Response Time (Typ.)	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Black
Radius	Panel Frame R1500 (Cover Glass R1493.4)
Mounting Options	VESA: 600 × 400 mm
Outline Dimensions (W × H × D)	1144.0mm × 670.0mm × 167.5mm
Power Supply	Input Voltage Range: +24VDC ± 5%
On Screen Display (OSD)	Control (back): Power, Auto, Up, Down, Menu
Power Consumption (Max.)	130W
System support	windows 7 or later, Linux 4.4 or later
Operating Altitude	≤3000m

Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	HDMI, DVI, DP, USB (Type B)
Accessories	Optional
Carton Box Dimensions (1 unit in one carton)	1269mm × 306mm × 824mm
Weight	Net: 27kg Gross: 35kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE, FCC
Warranty	1 year

Ordering Information		
Model	Part Number	Description
OTJ495-RC5000-UD5400-2.0	110303275R	49" "J type", UHD, 16:9, 500nits, PCAP, USB, HDMI/DVI/DP

Contact sales for other options

Optional Accessories		
Model	Part Number	Description
Adaptor	130104171R	G99-KEP150M-N001 Input:100-240V(VAC)- Output :24(VDC)-6.25A-150W-4PIN
Power Cable		1500mm
USB Cable	130300224R	USB Cable, 1500mm, male to male
DVI Cable	130300720R	DVI Cable, 1500mm ,male to male
HDMI Cable	130300881R	1500mm
DP Cable	130300932R	1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com