



ULO2405-A

24" TFT LCD, 1000nits LED Backlight, 1920x1080

The ULO2405-A is a 24 inch industrial grade sunlight readable LCD, with high brightness 1000 nits, it produce sharp images, crisp text and lifelike colors. The Ubipixel LED backlight technology ensures high reliability and low power consumption, suitable for outdoor application, kiosk, factory automation, military, transportation and gaming application.

Key Features

- High Brightness 1000 nits
- Sunlight Readable
- LED Backlight
- Low Power Consumption
- Wide Temperature(-20 °C ~ 70 °C)
- LCD Blacklight Defect Free(Hi-Tni 110°C)
- BL MTBF: 100,000 hours



Specifications

Model Name	ULO2405-A
Description	24" TFT LCD, 1000 nits LED Backlight, 1920x1080
Screen Size	24"
Display Area (mm)	531.36(H) x 298.89(V)
Brightness	1000 cd/m ²
Resolution	1920x1080
Aspect Ratio	16 : 9
Contrast Ratio	2600 : 1
Pixel Pitch (mm)	0.27675(H) x 0.27675(V)
Pixel Pre Inch (PPI)	92
Viewing Angle	178°(H),178°(V)
Color Saturation (NTSC)	84%
Display Colors	16.7M
Response Time (Typical)	25ms
Panel Interface	LVDS
Input Interface	HDMI, DP
Input Power	DC12V
Power Consumption	32W
OSD Key	4 Keys (Power Switch, Menu, +, -)
OSD Control	Brightness, Color, Contrast, Auto Turing, H/V Position...etc
Dimensions (mm)	558.6 x 325.8 x 50
Bezel Size(U/B/L/R)	13.45/13.46/13.62/13.62 mm
Weight (Net)	4 kg
Mounting	75x75, 100x100 mm
Operating Temperature	-20 °C ~ 70 °C
Storage Temperature	-30 °C ~ 80 °C

ULO= Panel + LED Driving Board + AD Control Board + Chassis

Specifications are subject to change without notice.



All brands or product names are trademarks or registered trademarks of their respective companies.




Mechanical Drawing

Outline Dimensions

Unit:mm





Note :

O.D. : OUTLINE DIMENSION

B.O. : BEZEL OPENING

V.A. : ACTIVE AREA

A : 4-M4_USER HOLE_MAX Depth=4mm

Ordering Information

Part Number	Description
ULO2405-AHB-T11	24",1000nits,1920x1080,T2070,HTni,LID24C,AD68862HP,O/B,DC12V,3in1,V1

Optional Accessories

Part Number	Description
810618301010	CABLE.POWER.AC.1830mm USA type
810618301090	CABLE,POWER,AC,1830mm Europe type
810618301050	CABLE.POWER.AC.1830mm UK type
810618301170	CABLE.POWER,AC,1830mm Australia type
810618301031	CABLE.POWER.AC.1830mm Japan type

Customer request

Touch	SCT (Single-Touch), PCT (Multi-Touch)
Glass	Tempered glass, AR coating.....