

MA-PBSA56-DP21

4.9-6.1 GHz Passive Antenna For Beam Steering, Azimuth Scan

Array antenna for Beam Steering Applications

- Dual polarized antenna four columns each.
- Azimuth scan



Specifications

Electrical

Individual Column	
Frequency range	4.9 – 6.1 GHz
GAIN, typ.	16 dBi
VSWR, max.	2:1
Polarization	Vertical and Horizontal
3 dB Beam-Width, Azimuth Plane, typ.	75°
3 dB Beam-Width, Elevation Plane, typ.	9°
Side Lobes, typ.	-11 dB
Cross Polarization, typ.	-15 dB
Port to Port Isolation, min.	-17 dB
Front to Back Ratio, typ.	-35 dB
Input power, max	10W
Input Impedance	50Ω
Lightning Protection	DC Ground

Mechanical

Dimensions (HxWxD)	370 x 370 x 40 mm (14.5" x 14.5" x 1.6")
Weight	2 kg
Connector	8 x N-type, Female
Back Plane	Aluminum protected through chemical passivation
Radome	UV Protected, Plastic
Mount	MNT-22

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel