


REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------



Wiring diagram

POWER SUPPLY

ELECTRIC VEHICLE

L1 6mm ² Brown		L1 6mm ² Brown
L2 6mm ² Black		L2 6mm ² Black
L3 6mm ² Gray		L3 6mm ² Gray
N 6mm ² Blue		N 6mm ² Blue
PE 6mm ² Yellow/Green		PE 6mm ² Yellow/Green
PP		PP
CP 0.75mm ² Red		CP 0.75mm ² Red

RC=220Ω±3%

RC=220Ω±3%

Laser Printing Front Note:




Laser Printing Back Note(Arial):

MEAC-T-032A-P1-03-5.0M-30AH
32A 440V AC
IEC 62196-2:2016
IP54
201xxxx-xxxx

Laser Printing Front Note(Arial):

MEAC-T-032A-V1-03-5.0M-30AH
32A 440V AC
IEC 62196-2:2016
IP54
201xxxx-xxxx

Laser Printing Back Note:



SEC B-B

Technical parameters

Rated voltage	440V AC
Rated current	32A
Temperature range	-30℃~+50℃
Insulate resistance	>5MΩ, 500V DC 1Min
Withstand voltage	L, N AND PE, 2500V AC 1Min L AND N, 2500V AC 1Min
Ingress protection	IP54
The insertion/pullout times	10000 TIMES
Insertion/pullout force	<100N
Standard	IEC 62196-2:2016

Customer Drawing

NOTES:

1. Cable: EN50620-2017 EV 5*6mm²+1*0.75mm² Black
2. RoHS Compliance

Size Measure Range	.XX	.X
≤6	±0.05	±0.10
6~30	±0.10	±0.20
30~120	±0.15	±0.30
120~400	±0.20	±0.50
400~1000	±0.30	±0.80
1000~2000	±0.50	±1.20
Angle Measure Range	.XX	.X
≤6°	±1.0°	±1.5°

PART NO.:

APPD: ZX 2220-1.16

CHKD: DT 2220-1.16

DRFT: XF LUO 2020-01-16

THIRD ANGLE PROJECTION



宁波高松电子有限公司

NINGBO DEGSON ELECTRICAL CO., LTD

NAME: EV ELECTRIC VEHICLE AND EV POWER SUPPLY (32A three-phase)
MEAC-T-032A-V1P1-03-5.0M-30AH

TITLE: Customer Drawing

DRAWING NO.:

DO NOT SCALE DRAWING

REV D0-1

SHEET 1/1

SCALE 1:6