

Overview

Product information

**RM-EBBL-2105-M-25050000002**

Right angle plug with direct plug in and out, rated current:50A; Rated voltage:110V DC; Withstand voltage:500V AC; Insulation resistance > 100M Ω ; Protection grade meet IP67 when mated; Mechanical life $\geq$ 3000 times; Pull out force > 25N; Operating temperature: - 40 ~ 105 $^{\circ}\text{C}$; Salt spray resistance : 72h; Flame retardant grade:UL94-v0; Environmental protection:RoHS. Color: lock ring - blue.

Product advantages

- ☒ Fast direct plug connection
- ☒ After plugging in place, it has auditory and visual feedback
- ☒ High plug life
- ☒ Beautiful appearance, more in line with human functional design

Product certification

RoHS

Technical data

Product drawing

3D model

□

Marking

classification	Insert
Series	DD
	DDD
	DM

technical parameter

insulation resistance	$\geq 100\text{M}\Omega$
Mechanical life	≥ 3000 次



Products weight (without packaging)	
Female/Male	Male
Dimension	3A
	32A
	6B
	10B
	16B
	24B
	32B
	48B
Number of positions	1 module
	3
	2
1	
Environmental parameters	
Degree of protection	MatchingIP67

Accessories

Business data	
Order number	25050000002
Packing unit	
Minimum order quantity	
Products weight (without packaging)	

