

LILLIPUT®

FS5

5.4" 1920×1200 Full HD monitor with silicone case



5.4" HDMI 2.0 & 3G-SDI On-Camera Monitor



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80
Fax. 01 47 01 16 22



e-mail : mse@es-france.com
Site Web : www.es-france.com



Excellent Display

The 5.4" 16:10 LTPS panel with 1920x1200 full HD resolution, 1100:1 high contrast, 160° wide viewing angles, 600cd/m² high brightness, 88% DCI-P3 color space, which offers outstanding viewing experience.



Color Space

Color space affects the richness of picture's color, the better color space, the better color reproduction.

- DCI-P3
- Rec.709
- FS5

HDR

When HDR is activated, the display reproduces a greater dynamic of luminosity, allowing lighter and darker details to be displayed more clearly. Effectively enhancing the overall picture quality. Support ST 2084 300 / 1000 / 10000 and HLG.



3D-LUT

3D-LUT is a table for quickly looking up and output specific color data. By loading different 3D-LUT tables, it can quickly recombine color tone to form different color styles. Built-in 3D-LUT, featuring 17 default logs and 6 user logs.



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80
Fax. 01 47 01 16 22



e-mail : mse@es-france.com
Site Web : www.es-france.com



3G-SDI INPUT / OUTPUT

SDI supports up to 1920×1080 60p/50p/30p/25p/24p(3G-SDI signal), and downward compatible with HD-SDI and SD-SDI.



3G-SDI signal can loop output to the other monitor or device when 3G-SDI signal input to this model.



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80
Fax. 01 47 01 16 22



e-mail : mse@es-france.com
Site Web : www.es-france.com



4K 60HZ HDMI 2.0

HDMI 2.0 supports up to 4096×2160 60p/50p/30p/25p/24p and 3840×2160 60p/50p/30p/25p/24p.



Some commercially DSLR Cameras (GH-5, R5...) have been upgraded to HDMI 4K 60Hz video output. It means this monitor is compatible with the best output video formats of DSLR cameras on the market.



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80
Fax. 01 47 01 16 22



e-mail : mse@es-france.com
Site Web : www.es-france.com

DISPLAY	Panel	5.4" LTPS
	Physical Resolution	1920×1200
	Aspect Ratio	16:10
	Brightness	600cd/m ²
	Contrast	1100:1
	Viewing Angle	160°/ 160° (H/V)
	HDR	ST 2084 300/1000/10000 / HLG
	Supported Log Formats	Slog2 / Slog3, Arrilog, Clog, Jlog, Vlog, Nlog or User...
	LUT Support	3D-LUT (.cube format)
INPUT	3G-SDI	1
	HDMI	1 (HDMI 2.0, supports up to 4K 60Hz)
OUTPUT	3G-SDI	1
	HDMI	1 (HDMI 2.0, supports up to 4K 60Hz)
FORMATS	SDI	1080p 60/50/30/25/24, 1080pSF 30/25/24, 1080i 60/50, 720p 60/50...
	HDMI	2160p 60/50/30/25/24, 1080p 60/50/30/25/24, 1080i 60/50, 720p 60/50...
AUDIO	Speaker	1
	Ear Phone Slot	1
POWER	Current	0.75A (12V)
	Input Voltage	DC 7-24V
	Battery Plate	NP-F / LP-E6
	Power Consumption	≤9W
ENVIRONMENT	Operating Temperature	-20°C~50°C
	Storage Temperature	-30°C~70°C
DIMENSION	Dimension(LWD)	154.5×90×20mm
	Weight	