

10.1" 1500 NITS ULTRA-BRIGHT

TOUCH CAMERA CONTROL MONITOR



1500 Nits



1920×1200



Touch Screen



50000h LED



Camera Control



3G-SDI / HDMI2.0

HT10S



LED PANEL LIFE TIME

A selection of high quality industrial LCD
with a longer life time.





1500 NITS

AUTO DIMMING

10.1" 1920×1200 physical resolution, with 1500 nits ultra brightness
for outdoor sunlight readable.

COLOR CALIBRATION

Color calibration supports the PRO/LTE version of ColourSpace CMS provided by Light Illusion.

*Default color calibration to 100%

HDR

Making lighter and darker details to be displayed more clearly. Support ST2084 300 / ST2084 1000 / ST2084 10000 / HLG

3D LUT

Built-in 3D-LUT, featuring 17 default logs and 6 user logs.



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80
Fax. 01 47 01 16 22



e-mail : mse@es-france.com
Site Web : www.es-france.com



TOUCH CONTROL

EASY TO USE

Easy and convenient touch commands to quickly wake up the menu on screen, then adjust camera assist functions, display and settings.



*Note: Touch function can be switched off by POWER button.



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80
Fax. 01 47 01 16 22



e-mail : mse@es-france.com
Site Web : www.es-france.com

CONTROL CAMERA

BY LANC CABLE

The LANC cable enables the monitor to be interfaced with the Sony video camera for the purpose of controlling some camera's functions.

HOW TO CONTROL?



ACTIONS FEEDBACK

Actions in the UI of camera control are reflected to video camera in real time.

UI FOR CAMERA CONTROL

Tap the "camera" icon on the right of menu to access the UI of camera control.



HOW TO CONTROL?

FOCUS	ZOOM	IRIS	
Controlling the focus of video camera.	Controlling the zoom in and out of video camera lens.	Controlling the aperture size of video camera.	Controlling the record function of video camera on and off.

*Note: Some cameras do not support all control functions.





3G-SDI

UP TO 1080P 60HZ

Equipped with 3G-SDI input and loop output interfaces, which support up to 1080p 60Hz video signal.



HDMI 2.0

UP TO 2160P 60HZ

Equipped with HDMI 2.0 input and loop output interfaces, which support up to 2160p 60Hz video signal.



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80
Fax. 01 47 01 16 22



e-mail : mse@es-france.com
Site Web : www.es-france.com

V-LOCK BATTERY PLATE

Supports all available V-lock batteries. Please note that oversized battery may take up space on external devices.

WIRELESS VIDEO TRANSMISSION

Any device with an NP-F series battery plate can be mounted.

NP-F BATTERY PLATE ADAPTER

This adapter allows for easy docking of external devices and powering external devices through the monitor.

VESA ADAPTER PLATE

This VESA adapter plate is used to enable the installation of V-lock battery plate.



Power to External Device

When external device and battery are installed at the same time, the battery can power not only monitor but also the external device.



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80
Fax. 01 47 01 16 22



e-mail : mse@es-france.com
Site Web : www.es-france.com

