

Magnet mount antenna

58 ... 300 MHz

KATHREIN

Antennen · Electronlc

Type No. K 51 16 4

Ord. No. 510 351

58 ... 300 MHz,
0 dB gain (ref. to quarter-wave
whip),
supply length 1380 mm

Connection	Cable RG 058-PE 4 meters long
Tuning	By shortening the whip (please note mounting instructions).
Maximum load	80 W (at 50 °C ambient temperature)
Mounting	By attaching the antenna to a steel surface of at least 1 m ² extension that should be as even as possible. Magnetic adhesive force: Approx. 200 N.
Max. diameter at base	95 mm
Material	Whip: Stainless steel. Swivel-joint parts: Chromium-plated brass. Magnetic base in shock-resistant plastic housing. Neoprene protection cover for the adhesive surface of the magnetic base.
Contents of delivery	Whip, base, cable, protection cover.
Components	Type No. (Ord. No.)
Whip	K 51 12 40 1 (510 349)
Protection cover	K 66 01 2 (510 156)



Danger

Use of antenna on stationary vehicle:
The magnet may lift off from vehicle even at slow
speed collision.



K 51 16 4



ES France - Département RF & Hyperfréquences
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 60
Fax. 01 47 01 16 22



e-mail : hyper@es-france.com
Site Web : www.es-france.com