


VC620-B Series

SMD VOLTAGE CONTROLLED QUARTZ CRYSTAL OSCILLATORS 表貼壓控石英晶體振盪器



FEATURES

- Compact size
- Low profile
- Pick and place assembly
- High reliability seam welded package

REACH
Compliant


RoHS II
Compliant

Parameters		Specifications
Output Waveform 輸出波型		CMOS
Frequency Range 頻率範圍		1.0MHz ~ 54.0MHz
Supply Voltage Range (Vdd) 工作電壓範圍		1.8V, 2.8V, 3.3V, 5.0V
Overall Frequency Stability with refer to 25°C** 相對於 25°C 的總頻率偏差 **		±25ppm, ±50ppm, ±100ppm
Operating Temperature Range 工作溫度範圍		-20°C ~ +70°C, -40°C ~ +85°C, -40°C ~ +125°C
Current Consumption (Idd) 消耗電流		20mA typ.
Rise & Fall Time 上 / 下沿時間		8ns Max.
Output Symmetry 輸出對稱性		40% ~ 60% , 45% ~ 55%
Output Voltage 輸出電壓	VOH	90% VDD
	VOL	10% VDD
Control Voltage Range 控制電壓範圍		0.90V±0.90V, 1.4V±1V, 1.65V±1.35V, 2.5V±2.0V
Absolute Pulling Range 絕對牽引範圍		50ppm Min.
Modulation Bandwidth (BW) 調制頻寬		5KHz Min.
Output Load 輸出負載		15pF
Start-up Time 起動時間		10ms Max.
Storage Temperature Range 儲存溫度範圍		-55°C ~ +125°C


** Inclusive of initial frequency tolerance at 25°C, operating temperature range, supply voltage change, load variation and 1st year aging.
包括在常溫頻率偏差、工作溫度範圍的頻率偏差、首年老化率、工作電壓及負載變化造成的頻率偏差。

Please consult our sales representatives for other specifications
如對其他規格查詢，請與我司銷售人員聯繫

DIMENSION (mm)




SOLDERING PATTERN (mm)



All specifications are subject to change without prior notice.
本公司保留修改規格的權利。

I INTERQUIP ELECTRONICS CO LTD
應達利電子有限公司

Flat A, 9th Floor, On Shing Industrial Building, 2-16 Wo Liu Hang Road, Fotan, N.T., Hong Kong
Tel: +852 2413 5515 Fax: +852 2413 7053 <http://www.interquip.com>



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 89
Fax. 01 47 01 16 22



e-mail : comp@es-france.com
Site Web : www.es-france.com