

RS720Q-E10-RS8U

Great Scalability and High Performance Computing (HPC)
with 4 nodes in a 2U Rack Server



2U4N



2



16

ASUS RS720Q-E10-RS8U is the ideal multi-node server powered by 3rd Gen Intel® Xeon Scalable processors, with each node supporting up to 16 DIMM, one PCIe® 4.0 slot, one OCP 3.0 and two M.2, and a total of eight NVMe/SAS/SATA drives.

FEATURE

- Powered by dual-socket 3rd Gen Intel Scalable processors with DDR4 Memory up to 3200MHz
- One PCIe 4.0 x16 slot and One OCP 3.0 module per node
- 8 x 2.5" Hot-swap Drive Bays support 8 x SATA/SAS/NVMe
- 3000W 80 Plus® Titanium power supplies
- Flexible air- and liquid-cooling solution
- Onboard ASUS ASMB10-iKVM
- ASPEED AST2600 controller

3rd Gen Intel Xeon Scalable processors

The RS720Q-E10-RS8U is built with the latest Intel® Xeon® Processor Scalable Family with 16 DDR4 Memory up to 3200MHz, and designed for the demand of high scalability, high density computing, and wide range of existing and emerging workloads.

PCIe 4.0 Ready

PCI Express® (PCIe®) 4.0 delivers 16 GT/s bandwidth, which is double the speed of PCIe 3.0, offering lower power consumption, better lane scalability and backwards compatibility.

Cooling Solutions

Air or liquid-cooled solutions. Asetek's Direct-to-Chip (D2C) liquid-cooling technology achieving lower power-usage effectiveness (PUE) and optimized TCO for data centers.

Enhanced Security

PF0 FPGA as the platform Root-of-Trust solution for firmware resiliency Trusted Platform Module 2.0 (TPM 2.0) to secure hardware through integrated cryptographic keys and offer regular firmware update for vulnerabilities.



RS720Q-E10-RS8U

Processor Support

SPECIFICATION

		2 x Socket P+ (LGA 4189) per Node
		3rd Gen Intel® Xeon® processor Scalable family (Up to 205W for air cooling, up to 350W for liquid cooling) UPI 11.2 GT/s
Core Logic		Intel® C621A PCH
Memory	Total Slots	16 (8-channel per CPU, 8 DIMM per CPU)
	Capacity	Maximum up to 8192GB per Node
	Memory Type	DDR4 3200/2933 RDIMM, LRDIMM, LR-DIMM 3DS
	Memory Size	128GB, 64GB, 32GB, 16GB RDIMM 256GB, 128GB, 64GB RDIMM 3DS 128GB, 64GB, 32GB LR-DIMM 3DS 512GB, 256GB, 128GB Intel® Optane™ DC persistent memory 200 Series (DCPMM)
Expansion Slots	Total PCI/PCI-X/PCI-E/PIKE Slots	Per Node:
	Slot Type	1 x PCI-E x16 (Gen4 x16 link), LP, HL 1 x OCP 3.0 Mezzanine (Gen4 x16 link) 2 x M.2 (Gen4 x4 link, up to 2280, PCIe, SATA)
Disk Controller	SATA Controller	The Same as SAS Controller
	SAS Controller	Per Node: Broadcom SAS3008 (Support RAID 0, 1) - 2 x SAS 12Gb/s ports or - 2 x SATA 6Gb/s ports
	NVMe Controller	Per Node: Intel® VROC (Support RAID 0, 1) - 2 x NVMe ports
Storage Bays	I = internal A or S will be hot-swappable	8 x 2.5" Hot-swap Storage Bays (SATA/SAS/NVMe Supported)
Networking	LAN	Per Node: 1 x Intel I210-AT Gigabit LAN controller 1 x Management Port
Graphic	VGA	Aspeed AST2600 64MB
Front I/O Ports		N/A
Rear I/O Ports		Per Node: 2 x USB 3.0 Ports 1 x VGA Port 1 x RJ-45 GbE LAN Ports 1 x RJ-45 Management Port
Switch/LED		Per Node: Rear: 1 x Power Switch/LED 1 x Q-Code/Port 80 LED Front: 1 x Power Switch/LED 1 x Location Switch/LED 1 x Message LED 2 x LAN LED
OS Support		Please find the latest OS support from http://www.asus.com/
Management Solution	Software	ASUS Control Center (Classic)
	Out of Band Remote Management	On-Board ASM10-iKVM for KVM-over-IP
Dimension		800mm x 444mm x 88mm(2U), 31.5" x 17.48" x 3.46
Net Weight Kg (CPU, DRAM & HDD not included)		35.5 Kg
Gross Weight Kg (CPU, DRAM & HDD not included, Packing included)		41.5 Kg
Power Supply (following different configuration by region)		1+1 Redundant 3000W 80 PLUS Titanium Power Supply Rating: 220-240 Vac, 15.5A (x2), 50-60Hz, Class I
Environment		Operation temperature: 10°C ~ 35°C (for < 205W CPU, with air cooling) Operation temperature: 10°C ~ 30°C (for 205W CPU, with air cooling) Operation temperature: 10°C ~ 35°C (for > 205W CPU, with liquid cooling)

