



AV800

Edge AI Inference Tesla T4 &

Xeon®D-2183IT



- Ultra-High Performance Intel® Xeon® D-2183IT (2.2GHz, 16 cores, 32 threads)
- NVIDIA TELS A T4 GPU Integrated (2560 CUDA, 16GB GDDR6)
- DDR4-2666 MHz
- NVMe for Fast & Mass Storage
- MIL-STD-810 Temperature, Shock, Vibration, MIL-STD-810 Salt Fog
- MIL-STD 461 EMI/EMC; MIL-STD 1275



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80
Fax. 01 47 01 16 22



e-mail : mse@es-france.com
Site Web : www.es-france.com

Features

Edge AI Inference, NVIDIA Tesla T4 & INTEL XEON D-2183IT

AV800 is 7STARLAKE ruggedized AI inference platform specifically designed for NVIDIA® Tesla T4 and supports Intel® XEON Skylake DE processor. Utilizing 7STARLAKE's Open Modular, Scalable Architecture, AV800 provide optimized cooling solution for Tesla T4, ensure the stable system operation in harsh environments. In addition to Tesla T4, AV800 provides one M.2 NVMe slot for fast storage access. Combining stunning inference performance, powerful CPU and expansion capability, it is the perfect ruggedized platform for versatile edge AI applications.

AV800 ruggedized AI inference platforms designed for advanced inference acceleration applications such as voice, video, image and recommendation services. It supports NVIDIA® Tesla T4 GPU, featuring 8.1 TFLOPS in FP32 and 130 TOPs in INT8 for real-time inference based on trained neural network model.



SPECIFICATIONS

GPU Architecture	NVIDIA Turing
NVIDIA Turing Tensor Cores	320
NVIDIA CUDA® Cores	2,560
Single-Precision	8.1 TFLOPS
Mixed-Precision (FP16/FP32)	65 TFLOPS
INT8	130 TOPS
INT4	260 TOPS
GPU Memory	16 GB GDDR6 300 GB/sec
ECC	Yes
Interconnect Bandwidth	32 GB/sec
System Interface	x16 PCIe Gen3
Form Factor	Low-Profile PCIe
Thermal Solution	Passive
Compute APIs	CUDA, NVIDIA TensorRT™, ONNX



Features

Ultra-High Performance Intel Xeon Performance with VMware Support



Skylake DE: The Intel® Xeon® processor D-2183IT product family is Intel's 64-bit system on a chip (SOC) and the first Intel® Xeon® SoC based on Intel* 14 nm silicon technology. This lineup offers hardware and software scalability from two up to sixteen cores, making it the perfect choice for a broad range of high-performing, low-power solutions that will bring intelligence and Intel® Xeon® reliability, availability, and serviceability (RAS) to the edge. For applications where space is a premium, an integrated Platform Controller Hub (PCH) technology and Intel® Ethernet in a ball grid array (BGA) package offer an inspiring level of design simplicity. The Intel® Xeon® processor Skylake DE product family is offered with a seven-year extended supply life and 10-year reliability for Internet of Things designs.

Design to Meet MIL-STD 810, MIL-STD 461

AV800 is designed to meet strict size, weight, and power (SWaP) requirements and to withstand harsh environments, including temperature extremes, shock/vibe, sand/dust, and salt/fog.

AV800 is MIL-461 EMI/EMC compliant rugged Edge AI Inference server. It passes numerous environmental tests including Temperature, Altitude, Shock, Vibration, Voltage Spikes, Electrostatic Discharge and more. The sealed compact chassis shields circuit cards from external environmental conditions such as sand, dust, and humidity.



Specifications

System

Processor	Intel® Xeon® Processor D-2183IT (Frequency 2.2GHz, Turbo Boost Frequency up to 3.0GHz), 16-Core, 32 Thread Support, 22MB Smart Cache
Memory type	2 x DDR4 up to 64GB
Chipset	SoC, integrated with CPU

GPU

NVIDIA	TESLA T4
Turning Tensor Cores	320
CUDA Cores	2560
Memory	16 GB GDDR6, 300 GB/sec

Graphics Output

1xVGA	ASPEED AST2500
Resolution	Up to 1920x1200@60Hz 32bpp

Storage

HDD/SSD	1x M.2 2280 M key NVMe socket (PCIe Gen3 x4) for NVMe SSD installation 2 x 2.5" SATA SSD (Easy Swappable)
---------	---

Side I/O

X1(2 x 10GbE Ethernet)	1x Amphenol TV07RW-13-35S (22PIN)
X2(VGA)	1 x Amphenol TV07RW-13-98S(10PIN) X3(USB3.0x2)
X3(USB3.0x2)	1 x Amphenol TV07RW-13-35SB(22PIN)
X4 (DC-IN)	1 x Amphenol TV07RW-13-04P (4PIN)
Button	1 x Power Switch with Dedicated LED
SSD Tray	2 x Dual 2.5" HDD/SSD Easy Swap Tray Dedicated LED
Dedicated LED	1 x Red LED (OVHT) ,1 x Green LEDs (SSD)

Power Requirement

Power Input	DC-DC 18 to 36V (300W max) MIL-STD 461
-------------	--



Applications, Operating System

Applications	C4ISR, Commercial and Military Platforms Requiring Compliance to MIL-STD-810 Process Control, where Harsh Temperature, Shock, Vibration, Altitude, Dust and EMI Conditions
Operating System	Windows 10 64Bit, Windows Server 2019 64bit, Windows 2016 64bit, Hyper-V Server 2016 R2, Ubuntu16.04.3 LTS/17.10/18.04.1LTS, Fedora 25/26, RedHat Linux EL 6.8/6.9/7.3/7.4/7.6, VMware ESXi 6.5u1, VMware ESXi 6.7U2

Physical

Dimension	405x 154 x316 mm(D x H x W)
Weight	15Kg (33.06lbs)
Chassis	Aluminum Alloy, Corrosion Resistant
Finish	Anodic aluminum oxide
Cooling	Natural Passive Convection/Conduction Cooling. No Moving Parts Ingress Protection
Ingress Protection	IP65

Environmental

Operating Test MIL-STD-810

Low air pressure	Method 500.5 Procedure 2	Operation/Air Carriage 4572m (15.000 ft)
Low Temperature	Method 502.5 Procedure 2	-20°C, 4 hours, ±3°C
High Temperature	Method 501.5 Procedure 2	+55°C, 4 hours, ±3°C
Humidity	Method 507.5	85%-95% RH without condensation, 24 hours/ cycle, conduct 10 cycle
Vibration	Method 514.6 Category 24	5-500Hz, Vertical 7.7Grms, 40mins x 3axis
Shock	Method 516.6	20 Grms, 11ms, 3 axes

Non-Operating Test MIL-STD-810

Low Temperature	Method 502.5	-33°C, 4 hours, change rate: ≤ 20°C/ Hour -15°C, 72hours (By request)
High Temperature	Method 501.5	+71°C, 4 hours, change rate: ≤ 20°C/ Hour
	Procedure 1	+68°C, 240 hours (By request)
Vibration	Method 514.6	5-500Hz, Vertical 7.7Grms, 40mins x 3axis



Shock	Method 516.6	20 Grms, 11ms, 3 axes
Salt Fog	Method 509.7	Salt Spray (50±5)g/L

MIL-STD 461

Conducted Emissions	CE102 curve	basic	10kHz – 30MHz
Power Leads			
Conducted Emissions	RE102-4		1.5HMz - 30MHz – 5GHz
Electric Field			
Radiated Susceptibility	RS103		1.5 MHz – 3GHz, 50 V/m equal for all frequencies
			2MHz – 80MHz, 50 V/m equal for all frequencies
			80MHz – 3GHz, 50 V/m equal for all frequencies
Electric Field			3GHz – 5GHz, 50 V/m equal for all frequencies
Electrostatic Discharge	EN 61000-4-2		Air DISCHARGE: 8 Kv, Contact discharge : 6kV
Electromagnetic compatibility	EN61000-4-4		Signal and DC Net: 1 kV
Electromagnetic compatibility	EN61000-4-5		Lead vs. ground potential 1Kv, ignal und DC Net: 1 kV
Radio disturbance	EN55022		Class A
Electromagnetic compatibility	EN61000-4-3		10V/m
Electromagnetic compatibility	EN 61000-4-5		Lead vs. ground potential 1Kv, ignal und DC Net: 0.5 kV

MIL-STD-1275 Specifications

Steady State	20V~33V
Surge Low	20V~33V
Surge High	18V/500ms



Appearance & Dimension

