



Portable **Density**/Specific Gravity/**Concentration** Meter

DenDi

**Observed
Density**

**Base
Density**

**Specific
Gravity**

**Alternative
Density**

Advantages

- Wide density range
- Simple in operation
- Removable float for easy cleaning
- Compact design; long-life battery
- "One Button" operation
- Simple user calibration

Applications

- Petroleum industry
- Milk
- Liquor; Beer; Wine
- Fruit juice
- Paint
- Perfumes; Cosmetics
- Oil products

**Correlation to
ASTM D1298**

**ASTM D1250
Tables**

API



ES France - Département Bio-tests & Industries
127 rue de Buzenval BP 26 - 92380 Garches




Tél. 01 47 95 99 90
Fax. 01 47 01 16 22



e-mail : bio@es-france.com
Site Web : www.es-france.com

les

Principle of operation



$$\rho = (m_f \cdot g - P) / V \cdot g$$

ρ - density of liquid

m_f - mass of the clean dry float

g - gravitational acceleration

P - force (weight) transmitted to the beam with balance

V - volume of the float

ρ_1, P_1 - density and weight of the air

ρ_1, P_1 - density and weight of the water

ρ_1, P_1 - max. measuring range of density and weight (2 000 kg/m³)

The operating principle of the device is – weighting of the glass float with filler fully immersed in liquid. It allows measuring observed density and temperature of wide range of opaque and transparent liquids. The buoyancy force of liquid acts on the float, which has precise weight and volume; the float's movement is transmitted to the beam with balance.

The electronics employ sophisticated signal processing and computational algorithms to deliver high accuracy measurements. The device has a rugged design with little need for service and easy cleaning. The calibration requires only distilled water. Built-in tables of water densities at testing temperatures and air density (average value for standard european conditions) allows to determine linear dependence of density and weight (see graph on top). Taken together these features result in a device with a long service life and very low cost of ownership.

Perfect substitution



Standard Glass Hydrometer

- Automatic measurements
- Simple in operation, safe
- Density/Concentration and Temperature measurements in one instrument
- Unit conversion
- Wide range of supported measuring units
- Automatic temperature compensation




- Connection to PC (saving, printing the

- Covered Density range:



Device description



Preparation of the Samples

- Liquids for measurements must be gas-free and their temperature must be equal to the ambient temperature $\pm 5^{\circ}\text{C}$.
- If the same beaker is used for various liquids – clean it thoroughly and dry before filling with new sample!
- For accurate sample preparation place the float into the beaker and fill it with measured liquid up to the top.
- Place the beaker to the special tray on the base of the device and set the float on the measuring arm - to ensure that the level sample is 2-4 mm above the float.
- Then you may take the float off the beaker and make a mark on the beaker with the help of marker for glass.

Preparation of the Device

- Make an external survey of the float and other submersible parts. They must be clean and dry, without mechanical injuries. Any dents or impurity adhered on the float will influence the accuracy of the density measurements!
- In case of impurity – wash the float in appropriate solvent and dry it with some non-fluffy material (paper towel, rags, etc.).
- Set and remove the float on the measuring arm – to check its free running. All the time take care of cleanness in the inlet of the measuring arm!
- Set the device on the workplace and adjust its horizontal position (in accordance with level vial) with the help of adjusting screws.
- Switch ON the device and warm it up for 10 minutes.

Two Step Operation

1



2



Specifications

Measuring range:

Density	0... 3 g/cm ³ (0... 3000 kg/m ³)
Density Standard	0.6... 1.2 g/cm ³ (600... 1200 kg/m ³)
Temperature	+15... +30°C (+59... +86°F)

Accuracy:

Density	±0.0005 or ±0.001 g/cm ³ (±0.5 or ±1.0 kg/m ³)
Temperature	±0.2°C (±0.4°F)

Repeatability:

Density	±0.00025 or ±0.00050 g/cm ³ (±0.25 or ±0.50 kg/m ³)
Temperature	±0.1°C (±0.2°F)

Resolution:

Density	0.0001 g/cm ³ (0.1 kg/m ³)
Temperature	0.01°C (0.02°F)

Supported Measuring Units

Observed/Relative Density: g/cm³, kg/m³, lb/gal, lb/ft³; API; SG
 Base Density: at 15°C, 20°C, 60°F; API60; SG60
 Tables ASTM D1250
 Alcohol Tables (volume%), °Bx, °P
 Temperature in °C or °F

Ambient Temperature +15... +30°C (+59... +86°F)

Sample Volume 100 ml (26.4·10⁻³ gal)

Power Supply NiMH 9V-150 mAh

Operating Time without Charging Appr. 12 hours

Dimensions (H x L x W), Weight 135 x 100 x 190 mm (5.3 x 3.9 x 7.5 in), 1.3 kg (2.7 lb)


Temperature Compensation Automatic

Viscosity Compensation Automatic

Data Handling

Backlighted LCD display
 Local memory for 998 results with date/time stamped
 Build in IR data port for data transfer to printer or PC
 Optional Windows - based software

Delivery Delivered in compact carrying case



SOFTWARE

Able to download the measurements to PC; Multifunctional software allows to proceed the measurements results in user-convenient form; Compatible for a Windows XP/Vista/7



IR PRINTER

Immediately printout the results; No need for PC



POCKET PC

Remote data transfer; Useful in field conditions; Software for data processing

For more information please visit www.lemis-usa.com



LEMIS USA, Inc

15556 Summit Park Dr., Suite 601

Montgomery

TX 77050 USA



ES France - Département Bio-tests & Industries
 127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 90
Fax. 01 47 01 16 22



e-mail : bio@es-france.com
Site Web : www.es-france.com