

High Frequency Tunable Bandpass — CTB Series

◆ Features:

- Manually Controlled
- High Performance Coaxial Cavity Design
- Multiple Tuning Ranges Available



◆ Specifications:

K&L Model Bandpass	Frequency Range (MHz)	Insertion Loss at f_0 (typical)	Insertion Loss at f_0 (max)	3 dB Bandwidth (nominal)	VSWR at f_0 (typical)	Approx. Size X Y Z (inches)
5CTB-2000/4000-1-N/N	2000 - 4000	1.25 dB	1.75 dB	1%	1.5:1	8.02 x 7.26 x 3.01
5CTB-4000/6000-1-N/N	4000 - 6000	2.25 dB	2.75 dB	1%	1.5:1	6.75 x 5.36 x 3.01
5CTB-6000/8000-1-N/N	6000 - 8000	TBD	TBD	1%	1.5:1	6.75 x 5.36 x 3.01
5CTB-2000/4000-2-N/N	2000 - 4000	0.75 dB	1.25 dB	2%	1.5:1	8.02 x 7.26 x 3.01
5CTB-4000/6000-2-N/N	4000 - 6000	1.25 dB	1.75 dB	2%	1.5:1	6.75 x 5.36 x 3.01
5CTB-6000/8000-2-N/N	6000 - 8000	TBD	TBD	2%	1.5:1	6.75 x 5.36 x 3.01
5CTB-2000/4000-5-N/N	2000 - 4000	0.4 dB	1.0 dB	5%	1.5:1	8.02 x 7.26 x 3.01
5CTB-4000/6000-5-N/N	4000 - 6000	0.5 dB	1.0 dB	5%	1.5:1	6.75 x 5.36 x 3.01
5CTB-6000/8000-5-N/N	6000 - 8000	TBD	TBD	5%	1.5:1	6.75 x 5.36 x 3.01
Filter Type:		5-Section Bandpass				
Shape Factor (30 dB to 3 dB/ 50 dB to 3 dB):		2.2:1/3.5:1				
Impedance:		50 ohms				
RF Connectors:		Type N standard, SMA optional				

◆ Applications:

- Test and Measurement Facilities
- Troubleshooting Co-location Environments
- Wireless Communications



ES France - Département RF & Hyperfréquences
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 60
Fax. 01 47 01 16 22



e-mail : hyper@es-france.com
Site Web : www.es-france.com