

ZR-1300A Aerosol Generator

01

Overview



ZR-1300A Aerosol generator is a special instrument for generating DOP aerosol by Laskin nozzle. The embedded adjusting valve could control the working of 4 or 10 nozzles. When the air flow is 1.4m³/min-56.6m³/min, the output aerosol concentration is 10µg/L-100µg/L. The performance of aerosol complies to national standards, and the device is suitable to institutes of medical device testing, centers of disease control, hospitals, pharmaceutical companies, HEPA filter manufacturers for leakage testing of clean rooms and HEPA filters.



02

Standard



GB 50591-2010 Code for construction and acceptance of cleanroom
YY0569-2005 Biosafety cabinet
GB/T13554-2008 High efficiency particulate air filter

03

Features



- ✓ Unique air channel design, stable air flow and balanced particle output.
- ✓ Generate multiple kinds of aerosols, DOP, DOS, PAO....
- ✓ Nebulizing concentration is adjustable in a wide range.



ES France - Département Bio-tests & Industries
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 90
Fax. 01 47 01 16 22



e-mail : bio@es-france.com
Site Web : www.es-france.com

04

Technical Parameter



Parameter	Range	Resolution	Error
Working pressure	(0~600) kPa	1 kPa	±7kPa
Particle output range	(1.4-56.6) m ³ /min		
Particle concentration	100µg/L (air flow is 5.6 m ³ /min)		
Particle concentration	10µg/L (air flow is 56.6 m ³ /min)		
Generating method	4-10 Laskin nozzle		
Compressed air	Embedded compressor		
Air type	Multiple size of particles (Cold generating)		
Dimension	(Length 200×Width 500×Height 280) mm		
Noise	<65dB(A)		
Weight	About 18Kg		
Working power	AC220V±10%, 50Hz		
Power consumption	≤500W		

