

• **Different forms of samples can be measured.**

Most samples which vaporize only moisture and cause no hazardous reaction under heating can be measured.



Grain

Food

Chemical



Powder

Particles

Paste/Liquid


Option



VZ-330 Printer



Windshield with Deodorizer FW-100



Printing example

Specifications

Measurement format	Evaporation weight loss method (Heat drying and weight loss method)
Measurement object	Powder particle, liquid, paste, etc.
Sample weight	0.5~120g using selective weight sampling method
Minimum displayable units	Switch between moisture 0.01 % / 0.1 %, mass 0.001 g
Measurement range	0 - 100 % (wet base, solids), 0 - 500 % (dry base)
Reproducibility (Standard deviation)*1	Sample mass 5 g and above : 0.05 % Sample mass 10 g and above : 0.02 % including water content
Measurement modes	<ul style="list-style-type: none"> Automatic halting mode Timed halting mode (with measurement times of 1~240 minutes or continuous measurement mode, with a max. measurement time of 12 hours) High-speed drying mode (used with either automatic or timed halting mode) Low-speed drying mode (used with either automatic or timed halting mode) Stepped drying mode (5 steps) Predictive (comparative) measuring mode
Temperature range	30-180°C in 1-degree increments when using a thermistor
Display	Backlight LCD display (137 x 43 mm)
External output	RS-232C interface
Temp. / humidity operating range	5 - 40 °C, maximum of 85 % RH
Heat source	Mid-infrared quartz heater (200 W x 2)
Temperature sensor	Thermistor
Power supply	AC100-120 V / 220-240 V (50/60 Hz)
Power consumption	Maximum 900 W
Weight and external dimensions	Net : 5.4 kg / Gross : 9.5kg, 220 x 415 x 220 mm (W x D x H)
Sample dish	SUS sample dish (Diameter : 130 mm ; Depth 13 mm)
Items included	2 sample dishes, 2 sample dish handlers, sample dish tray, wind shield, power cord, spoon & spatula set, 2 spare fuses (8 A), 2 packages of aluminum foil sheets (10 per package), glass fiber sheets (10 sheets), operating manual
Optional equipment	Printer set (includes a printer "VZ-330", a interface cable "VZC-14", printer paper, and an AC adapter), Printer paper (10 rolls), aluminum foil sheets (500 sheets), RS-232C cable "VZC-52", Temperature sensor testing kit "GF-100", Data logger software "KDL-01", Sample crusher "TQ-100", Windshield with Deodorizer "FW-100"

*1. As per Kett's in-house stipulated measurement conditions and standard samples.

Safety precautions

For safe operation, ensure you read the Operating Manual before use.
Do not attempt to measure material that will cause dangerous chemical reactions on heating. Further, the tester becomes very hot, so please take precautions against burns and /or fire.

Requests

KETT ELECTRIC LABORATORY
1-8-1 Minami-Magome Ota-Ku, Tokyo 143-8507 Japan
Tel. +81-3-3776-1121 Fax. +81-3-3772-3001
URL <http://www.kett.co.jp/> E-mail overseas@kett.co.jp

Management System Enhancement Department of the Japanese Standards Association (JSA) registers the Quality Management System of the above organization, which conform to JIS Q 9001, ISO 9001.

The Scope of the Registration.
Design, development and production management of Moisture Testers, NIR Composition Analyzers, Grain Inspectors and Coating Thickness Testers. Calibration and repair of Moisture Testers, NIR Composition Analyzers, Grain Inspectors and Coating Thickness Testers.

VEGETABLE OIL INK This brochure uses environmentally friendly "vegetable soy ink" and waste paper blend recycled paper.

● To improve the product, specifications and the external appearance may be changed without notice. In
● For enquiries regarding this product, please contact us at the address above, or by e-mail.

FD-720

Infrared Moisture Analyzer



ES France - Département Bio-tests & Industries
127 rue de Buzenval BP 26 - 92380 Garches


Tél. 01 47 95 99 90
Fax. 01 47 01 16 22

e-mail : bio@es-france.com
Site Web : www.es-france.com

FD-720

Infrared Moisture Analyzer

FD-720 can change the moisture display from normal 0.1% to high accuracy 0.01% resolution. To realize its high accuracy, the 1mg resolution balance unit is installed. The heater source is newly developed, a large 400watts Mid-wave infrared quartz heater controlled by the software for the drying process. It has "High-speed drying mode" that can reduce much of the measurement time for suitable sample materials. 10 measurement conditions can be saved in the instrument memory so that you don't have to enter the condition manually every time for each sample. The optional data logger software enables the data transfer linked with PC. The optional printer VZ-330 prints out the measurement result in a graph or numerical format. FD-720 is designed for all quality control and testing divisions where the most accurate moisture measurement is required.



Accurate moisture measurement with new weight sensor


- Large sample dish allows even a large amount of sample to be placed evenly in a thin layer. The result is accurate and fast measurements.
- Mid-wave infrared quartz heater provides effective drying without interference for a wide range of samples. Besides the excellent drying performance, it offers a long operational life of 20,000 to 30,000 hours.
- The internal precision weighing balance is engineered with a UniBloc cell. The mechanism provides excellent stability and a long operational life against repeated temperature changes.
- Digital control allows a selection of measurement modes. 10 measurement conditions can be stored for quick recall. Select one of the 9 combinations of drying and halting modes to optimize the measurement of your sample.
- Weight loss rate in the previous thirty seconds is monitored and visually presented in the bar graph display. This feature is especially useful to show that the measurement is close to completion.
- Optional Kett's unique data logger software "KDL-01" can transfer measurement data to an application such as Excel.
- A larger sample dish contributes to accurate measurements, but the larger heat capacity normally produces larger zero drift due to temperature fluctuation. The FD-720 is equipped with a unique auto-taring mechanism, which adjusts the zero drift automatically and ensures high accuracy, even with a larger sample pan.
- Bias function allows adjustment to the data obtained by other measuring methods or other testers.
- Large backlit LCD is easily read even under poor lighting conditions.

UniBloc is a trade name of Shimadzu Corporation.
MS Excel is a trademark of Microsoft Corporation.

Choice of measuring modes meets your application.


Automatic halting mode

The sensor will automatically halt if the 30s interval moisture change (fluctuation range%) goes below the set value.




Low-speed drying mode

Slowly dries samples in which surface membrane forms or samples that may break down at high temperatures.




Timed halting mode

Sensor will halt at the pre-set time (t1).




Stepped drying mode

Measures drying conditions in steps, and measures samples that contain a large amount of water, such as surface water or crystallized water.




High-speed drying mode

Shortens the measuring time by the high-speed drying during the initial drying stage, after which when the moisture is reduced, the set temperature is returned to normal.



Predictive (comparative) measuring mode

Predicts future changes from the drying process and determines a measurement value (Mp). Measuring time is shortened.



Bar graph display monitors moisture vaporization

Moisture vaporization rate display

In drying by infrared heater, a large amount of moisture vaporizes in early stage and vaporization slows towards the end of measurement. The M curve in Figure1 shows a typical vaporization of moisture. M indicates the rate of vaporization. Monitoring M makes it possible to gauge how close the measurement is to completion. The bar graph display makes it visible. (Figure2)

Figure1





Figure2



Meets demands of various industries and fields

Pharmaceuticals, agriculture, food processing, textiles, chemicals, fertilizer, paper, construction.

* Material that will not cause dangerous chemical reactions when heated.

* Material that will dry due to evaporation of water or other substance that is to be measured.

