

Quick Test Adapters

DATA SHEET / 2B-060



ES France - Département RF & Hyperfréquences
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 60
Fax. 01 47 01 16 22



e-mail : hyper@es-france.com
Site Web : www.es-france.com

Quick Test Adapters

8006 SERIES (U.S. PATENT NO.
6,210,221) 7906 SERIES (U.S.
PATENT NO. 8,827,743)

Description

The male connector incorporates a quick connect design that provides for a push-on/pull-off capability that mates with any commercially available 2.4mm and 3.5mm connectors. The optional quick 1-1/2 turn twist nut combines the best of both worlds allowing quick connect or disconnect with the increased accuracy of a thread-on connector. In addition to the no nut and quick turn nut designs, a guide sleeve configuration is available to provide a self-aligning capability required in automated test stations.

The push-on connector offers excellent repeatability and long life making these adapters ideal for use in a production environment. The nut can also be torqued to 8 in. lbs making them suitable for test port applications where a calibration is required. The connectors come in four configurations: no nut, a 3/8" diameter nut, a 9/16" diameter nut, and a guide sleeve configuration.

Features

- > Quick, Easy Push-On/Pull-Off Design
- > Designed for Durability and Long Life (3,000 Connect/Disconnect Cycles)
- > Excellent Repeatability/Low VSWR
- > Guide Sleeve Design for Automated applications



8006E1
No Nut

8006E11
3/8" Nut

8006E21
9/16" Nut

8006Q1
Guide
Sleeve

7906E1
No Nut

7906E11
3/8" Nut

7906E21
9/16" Nut

7906Q1
Guide
Sleeve

Repeatability*

MODE	
Push-On	> 40 dB
Torqued to 8 in. lbs	> 50 dB
Hand Torqued	> 50 dB

*Repeatability is based on a minimum of 3,000 connect/disconnect cycles.

Available Models

MODEL	ADAPTS		FREQUENCY RANGE (GHz)	MAXIMUM VSWR (GHz)
	SIDE A	SIDE B		
8006E1 8006E11 8006E21 8006Q1	QT3.5mm™ (m) with no nut QT3.5mm™ (m) with 3/8" diameter nut QT3.5mm™ (m) with 9/16" diameter nut QT3.5mm™ (m) guide sleeve	3.5mm (f)	DC — 26.5 ¹	DC — 16.0 ≤ 1.05 16.0 — 26.5 ≤ 1.08 26.5 — 34.0 ≤ 1.12
7906E1 7906E11 7906E21 7906Q1	QT2.4mm™ (m) with no nut QT2.4mm™ (m) with 3/8" diameter nut QT2.4mm™ (m) with 9/16" diameter nut QT2.4mm™ (m) guide sleeve	2.4mm (f)	DC — 50	DC — 26.5 ≤ 1.08 26.5 — 40 ≤ 1.12 40 — 50 ≤ 1.15

¹ Slightly reduced VSWR specifications to 34 GHz.



VISIT OUR WEB STORE
TO LEARN MORE ABOUT
OUR PRODUCTS



www.maurymw.com



ES France - Département RF & Hyperfréquences
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 60
Fax. 01 47 01 16 22



e-mail : hyper@es-france.com
Site Web : www.es-france.com

CONTACT US:

W / maurymw.com
E / maury@maurymw.com
P / +1-909-987-4715
F / +1-909-987-1112
2900 Inland Empire Blvd
Ontario, CA 91764

