### GB NANO H

3 Channels GAS Mixer

Max Flow Rate: Up to 500 mL/min Custom Firmware and Software Multi-System Cell Expansion (from 2 up to 4) No Specific Skills are required IQ OQ GMP Ready Smart Alarms.



www.mcginst.com info@mcqinst.com

### For CELL EXPANSION SYSTEMS

Manage the flow of N2, O2, CO2 or Dilute Air.



#### GB NANO H SUPPORTS FROM 2 UP 4 CELL EXPANSION SYSTEMS

Designed specifically for cell expansion processes, the GB Nano H offers precise control and blending of gases, creating optimal growth conditions. This versatility, coupled with its ability to connect from 2 up to 4 cell expansion systems simultaneously, allows for the creation of various conditions, including Hypoxia and Anoxia, using Pure Gas Cylinders or diluting Air from the wall-mounted pipe.





## Flexibility and Multi-System Cell Expansion.

MCQ Instruments offers the best, cheapest and fastest solutions to manage, control, measure the flow of pure cylinders of N2, O2, and CO2 in order to create specific conditions such as Hypoxia, Anoxia, or any other. Additionally, the Gas Mixer enables the dilution of Air to attain the desired gas composition.

The GB Nano H supports from 2 up to 4 cell expansion systems for increased capacity.

### Gases:

N2, O2, CO2, Air, H2

(additional gases supported on request)





### **Custom Firmware**

Our custom software and firmware give you significantly more control over your cell culturing compared to the other regular Gas Mixers.

Get alerted to potential issues, and connect our Gas Mixer with various cell expansion systems. More features are under development (coming soon).

### Smart Alarms.

Our advanced Gas Mixer is equipped with intelligent alarms that monitor the gas flow, ensuring the safety and stability of the cell expansion experiments:

- NO FLOW: Indicating disconnected gas cylinders, or complete obstructions.
- UNDER FLOW: Identifying gas supply restrictions or approaching empty gas cylinders.
- OVER FLOW: Alerting to sudden pressure surges.
- INSTABILITY: Detecting irregular pressure regulation or control issues.





# Touch Display & PC Software Included.

The GB Nano H is a standalone device that allows you to control all parameters and access all main features through its touch display.

For Advanced functionality or to control the instrument via PC, we also provide MCQ Mixture Creator.



### Certified Products.











## No Specific Skills Required

It is an easy to use and FULLY AUTOMATED Gas Mixer.

No specific skills are required to start creating your Gas Mixtures. Fast, stable, accurate. It assures top performances even when managing low flow rates.

## IQ OQ GMP Ready.

We ensure adherence to rigorous manufacturing processes through a comprehensive validation system:

Our "IQ OQ GMP Ready" slogan reflects our unwavering commitment to quality and compliance. It signifies that our products have undergone rigorous testing and meet the highest standards of manufacturing practices, ensuring the safety and reliability you demand for your research endeavors.





## Accurate. Compact. Reliable.

"The MCQ Gas Blender Nano H is the ultimate solution specifically designed for laboratories, for non - corrosive gas mixings and dilutions. It is an innovative all - in - one replacement for traditional pre-mixed cylinders solution."

## Specifications.

Accuracy: (for each channel)	5-100% FS: 1% of SP < 5% FS: 0,5% of FS
Repeatability:	0,10% of reading
Response time: (for each channel)	100 ms

N2, 20 °C, 101.325 kPa (1 atm):

Operation Pressure:	Max 3 bar
Working Temperature:	15 - 35 ℃

Mass Flow Rates:	0,5 - 500 mL/min
(for each channel)	on N2 (Standard)

<b>Total Mixture</b>	Flow Rate:	Up to 500 mL/min
101011111111111010	11011 120101	Op 10 000 milly mill

Gases:	N2, O2, CO2, Air, H2 (additional gases supported on request)

Compatibility:	Protibus,	Modbus,	Simulink,	Python

Communication:	USB PC Interface RS485 with open
	proprietary protocol

Alarms:	4 - No Flow, Under Flow,
	OverFlow and Instability

Fittings:	PTC (Push to Connect): EU: Inlet 6 mm - Outlet 1/4"
	US & APAC: Inlet &Outlet 1/4"

Inlet Gas Channel: 3 Input	Inlet	Gas	Channel:	3	Inputs
----------------------------	-------	-----	----------	---	--------

Outlet Gas Channel:	1 Output of mixed gases
---------------------	-------------------------

User Interface:	Gas mixing software. Touch Display.
-----------------	-------------------------------------

Certifications:	CE, TUV, cTUVUS, Made in Italy
-----------------	--------------------------------



High Accuracy Native calibration on available gas with 1% of accuracy for each channel



Lab in a Box All the tools in a single, compact and easy to transport box.



Sofware Bundle Mixture Creator is an user friendly interface, with which you can easily manage any gas mixing process.



GB Family We have as many solutions as many are your needs.

www.mcqinst.com - info@mcqinst.com