


COMMON MODE CHOKE (Flat Wire Winding)



- Core Size : SQ1212
- Rated Current : 1.5 A
- Dielectric strength : 2000Vrms
- Rated Voltage 250V AC
- Operating Temperature : -20~120°C
- Application : large current & small size power supply

ELECTRICAL SPECIFICATIONS @25°C

Model No.	I RMS (Amps)	OCL(mH min)	MAX DCR(mΩ)	Inductance Difference(uH max)
SQ1212V203	1.5	20	260	200
SQ1212V103	1.5	10	230	200
SQ1212H203	1.5	20	260	200
SQ1212H103	1.5	10	230	200

* For RoHS compliant products,





a.)Ordering code (Manufacturer Part Number): TG-Model No. ex. TG-SQ1212V203

b.) Solder : Sn/Cu; c.)Date Code suffix to "G"





* Inductance test at 1KHz, 0.25V.

DIMENSIONS & SCHEMATICS

V : Vertical type



H : Horizontal type



UNIT : mm

*Specifications are subject to change without prior notice.

DATA SHEET 09-34 Mar./22

1 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 89
Fax. 01 47 01 16 22





e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)

Attenuation (typical values at $Z=50\Omega$)

———— asymmetrical, all branches in parallel (common mode)

- - - - - symmetrical (differential mode)



DATA SHEET 09-34 Mar./22
2 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches




Tél. 01 47 95 99 89
Fax. 01 47 01 16 22



e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)



- Core Size : SQ1515
- Rated Current : 1.5 ~ 2.5A
- Dielectric strength : 2000Vrms
- Rated Voltage 250V AC
- Operating Temperature : -20~120°C
- Application : large current & small size power supply

ELECTRICAL SPECIFICATIONS @25°C

Model No.	I RMS (Amps)	OCL(mH min)	MAX DCR(mΩ)	Inductance Difference(uH max)
SQ1515V203	1.5	20	390	200
SQ1515V103	1.5	10	360	200
SQ1515V852	1.8	8.5	170	200
SQ1515V552	2.5	5.5	115	200
SQ1515H203	1.5	20	390	200
SQ1515H103	1.5	10	360	200
SQ1515H852	1.8	8.5	170	200
SQ1515H552	2.5	5.5	115	200

* For RoHS compliant products,

a.) Ordering code (Manufacturer Part Number): TG-Model No. ex. TG-SQ1515V203




b.) Solder : Sn/Cu; c.) Date Code suffix to "G"

* Inductance test at 1KHz, 0.25V.






DIMENSIONS & SCHEMATICS

V : Vertical type



H : Horizontal type



UNIT : mm

*Specifications are subject to change without prior notice.

DATA SHEET 09-34 Mar./22
3 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 89
Fax. 01 47 01 16 22






e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)

Attenuation (typical values at $Z=50\Omega$)

———— asymmetrical, all branches in parallel (common mode)

- - - - - symmetrical (differential mode)



DATA SHEET 09-34 Mar./22
4 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 89
Fax. 01 47 01 16 22




e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)

Attenuation (typical values at $Z=50\Omega$)

—— asymmetrical, all branches in parallel (common mode)

- - - - - symmetrical (differential mode)



DATA SHEET 09-34 Mar./22
5 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches




Tél. 01 47 95 99 89
Fax. 01 47 01 16 22



e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)



- Core Size : SQ1918
- Rated Current : 1.0~ 2.5A
- Dielectric strength : 2000Vrms
- Rated Voltage 250V AC
- Operating Temperature : -20~120°C
- Application : large current & small size power supply

ELECTRICAL SPECIFICATIONS @25°C

Model No.	I RMS (Amps)	OCL(mH min)	MAX DCR(mΩ)	Inductance Difference(uH max)
SQ1918V243	1.0	24	460	200
SQ1918V203	1.5	20	230	200
SQ1918V133	2.5	13	150	200
SQ1918H243	1.0	24	460	200
SQ1918H203	1.5	20	230	200
SQ1918H133	2.5	13	150	200

* For RoHS compliant products,

a.) Ordering code (Manufacturer Part Number): TG-Model No. ex. TG-SQ1918V243


b.) Solder : Sn/Cu; c.)Date Code suffix to "G"

* Inductance test at 1KHz, 0.25V.




DIMENSIONS & SCHEMATICS

V : Vertical type



H : Horizontal type



UNIT : mm

*Specifications are subject to change without prior notice.

DATA SHEET 09-34 Mar./22
6 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 89
Fax. 01 47 01 16 22






e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)

Attenuation (typical values at $Z=50\Omega$)

———— asymmetrical, all branches in parallel (common mode)

- - - - - symmetrical (differential mode)



DATA SHEET 09-34 Mar./22
7 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 89
Fax. 01 47 01 16 22



e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)



- Core Size : SQ2418
- Rated Current : 1.7 ~ 5A
- Dielectric strength : 2000Vrms
- Rated Voltage 250V AC
- Operating Temperature : -20~120°C
- Application : large current & small size power supply

ELECTRICAL SPECIFICATIONS @25°C

Model No.	I RMS (Amps)	OCL(mH min)	MAX DCR(mΩ)	Inductance Difference(uH max)
SQ2418V153	1.7	15	210	200
SQ2418V123	2.3	12	140	200
SQ2418V502	5	5	80	200
SQ2418H153	1.7	15	210	200
SQ2418H123	2.3	12	140	200
SQ2418H502	5	5	80	200

* For RoHS compliant products,

a.) Ordering code (Manufacturer Part Number): TG-Model No. ex. TG-SQ2418V153





b.) Solder : Sn/Cu; c.)Date Code suffix to "G"

* Inductance test at 1KHz, 0.25V.






DIMENSIONS & SCHEMATICS

V : Vertical type



H : Horizontal type



UNIT : mm

*Specifications are subject to change without prior notice.

DATA SHEET 09-34 Mar./22
8 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 89
Fax. 01 47 01 16 22






e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)

Attenuation (typical values at $Z=50\Omega$)

———— asymmetrical, all branches in parallel (common mode)

- - - - - symmetrical (differential mode)



DATA SHEET 09-34 Mar./22
9 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches




Tél. 01 47 95 99 89
Fax. 01 47 01 16 22



e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)



- Core Size : SQ2820
- Rated Current : 8 ~ 9A
- Dielectric strength : 2000Vrms
- Rated Voltage 250V AC
- Operating Temperature : -20~120°C
- Application : large current & small size power supply

ELECTRICAL SPECIFICATIONS @25°C

Model No.	I RMS (Amps)	OCL(mH min)	MAX DCR(mΩ)	Inductance Difference(uH max)
SQ2820VA902	8	9.0	50	200
SQ2820H902	8	9.0	50	200
SQ2820VA702	9	7.0	40	200
SQ2820H702	9	7.0	40	200

* For RoHS compliant products,

a.) Ordering code (Manufacturer Part Number): TG-Model No. ex. TG-SQ2820VA902


b.) Solder : Sn/Cu; c.)Date Code suffix to "G"

* Inductance test at 1KHz, 0.25V.




DIMENSIONS & SCHEMATICS

V : Vertical type



H : Horizontal type



UNIT : mm

*Specifications are subject to change without prior notice.

DATA SHEET 09-34 Mar./22
10 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 89
Fax. 01 47 01 16 22





e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)

Attenuation (typical values at $Z=50\Omega$)

———— asymmetrical, all branches in parallel (common mode)

- - - - - symmetrical (differential mode)



DATA SHEET 09-34 Mar./22
11 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches




Tél. 01 47 95 99 89
Fax. 01 47 01 16 22



e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)



- Core Size : SQ3129
- Rated Current : 10~12A
- Dielectric strength : 2000Vrms
- Rated Voltage 250V AC
- Operating Temperature : -20~120°C
- Application : large current

ELECTRICAL SPECIFICATIONS @25°C

Model No.	I RMS (Amps)	OCL(mH min)	MAX DCR(mΩ)	Inductance Difference(uH max)
SQ3129H702A	10	7.0	30	200
SQ3129H502A	12	5.0	25	200

* For RoHS compliant products,


a.) Ordering code (Manufacturer Part Number): TG-Model No. ex. TG-SQ3129H502A

b.) Solder : Sn/Cu; c.) Date Code suffix to "G"

* Inductance test at 1KHz, 0.25V.



DIMENSIONS & SCHEMATICS



UNIT : mm

*Specifications are subject to change without prior notice.

DATA SHEET 09-34 Mar./22
12 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 89
Fax. 01 47 01 16 22





e-mail : comp@es-france.com
Site Web : www.es-france.com

COMMON MODE CHOKE (Flat Wire Winding)

Attenuation (typical values at $Z=50\Omega$)

———— asymmetrical, all branches in parallel (common mode)

- - - - - symmetrical (differential mode)



DATA SHEET 09-34 Mar./22
13 OF 13



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.net> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C



ES France - Département Composants & Modules
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 89
Fax. 01 47 01 16 22



e-mail : comp@es-france.com
Site Web : www.es-france.com