

comemso

Easy Chester® DC Load

Technical datasheet



ES France - Département Puissance Energie
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 45
Fax. 01 47 01 16 22



e-mail : tem@es-france.com
Site Web : www.es-france.com

Easy Chester® DC Load

118-3-001 –
Easy Chester® DC Load



Technical Data



Application	Applicable for charging station test, supporting 400 V and 800 V technology
Charging capacity	30 kW with one load or up to 60kW with two loads in parallel 400 V technology adjustable in 2 kW steps until 30 kW 800 V technology adjustable in 4,5 kW steps until 31,5 kW DC Load required
Charging time	continuous operation for CCS / NACS
Charging technologie	400 V and 800 V technology
AC Supply	85 - 245 V AC
Power consumption	Max. 60 VA – in rush current might be higher
Protection class	IP 20
Temperature range	0 ... + 50 °C / 32 - 122 °F
Humidity	80% non-condensing
Transportability	Movable case
Weight	48 kg
CE conformance	MC: IEC61326-1 Safety: ISO61010-1

comemso

comemso electronics GmbH
Karlsbader Str. 13 | 73760 Ostfildern
Germany
Telefon +49 711 / 982 98 -200
sales@comemso.com



ES France - Département Puissance Energie
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 45
Fax. 01 47 01 16 22



e-mail : tem@es-france.com
Site Web : www.es-france.com