

COAXIAL ADAPTER, N - SMA, 50 Ohm, plug / jack (male / female)

33_N-SMA-50-1/113_N

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials

**Product configuration**

Interface type	Gender	Standard
N	plug (male)	IEC 61169-16_MIL-STD-348A/304_CEECC 22210
SMA	jack (female)	IEC 60169-15_MIL-STD-348A/310_CEECC 22110

Interface and material data

N		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
SMA		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	

Electrical data

Impedance	50 Ω
Interface frequency	18 GHz

Mechanical data

Weight	0.0299 kg
Mating cycles	500

HYPER-SOUND

COAXIAL ADAPTER, N - SMA, 50 Ohm, plug / jack (male / female)

33_N-SMA-50-1/113_N

Environmental data

Operation temperature	-65 °C ... 165 °C
-----------------------	-------------------

Ordering Information Table

Item number	Item description	Packaging type
22652905	33_N-SMA-50-1/113_NE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2195 / Date of publication: 27.05.2024 / uncontrolled copy

