

COAXIAL ADAPTER, N, 50 Ohm, jack / jack (female / female)

31_N-50-0-2/133_N-1

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials

**Product configuration**

Interface type	Gender	Standard
N	jack (female)	IEC 61169-16_MIL-STD-348A/304_CECC 22210
N	jack (female)	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Interface and material data

N		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
N		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Electrical data

Impedance	50 Ω
Interface frequency	12.4 GHz

Electrical Data (frequency related)

Frequency range	Return loss	VSWR
0 GHz ... 2 GHz	30 dB	1.07
2 GHz ... 8 GHz	15 dB	1.43
8 GHz ... 12.4 GHz	10 dB	1.92

HYPER-SUINED

ES France - Département RF & Hyperfréquences
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 60
Fax. 01 47 01 16 22



e-mail : hyper@es-france.com
Site Web : www.es-france.com

COAXIAL ADAPTER, N, 50 Ohm, jack / jack (female / female)

31_N-50-0-2/133_N-1

Mechanical data

Weight	0.0411 kg
Mating cycles	500

Environmental data

Operation temperature	-65 °C ... 165 °C
-----------------------	-------------------

Ordering Information Table

Item number	Item description	Packaging type
22649845	31_N-50-0-2/133_NY	Tray

HUBER+SÜHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2400 / Date of publication: 27.05.2024 / uncontrolled copy

